

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 30 S., R. 5 W.

## CHAINS

34.30 Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.

35.20 Spur, slopes N.; desc. 75 ft. over W. slope.

38.45 Ravine, drains NW.; asc. 5 ft. over NE. slope.

39.16 The cor. of secs. 26, 27, 34, and 35, perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, monumented with an iron pipe,  $\frac{1}{2}$  ins. diam., protruding 5 ins. above ground, firmly set, from which the remaining original bearing trees:

A root hole, bears S. 80° E., 40 lks. dist., alongside of which is an uprooted and rotted oak, 18 ins. diam., with illegible scribe marks visible on opened and rotted blaze.

A root hole, bears S. 10° W., 50 lks. dist., alongside of which is an uprooted and rotted oak, 14 ins. diam., with scribe marks S34 BT visible on opened and rotted blaze.

and bearing trees mkd. by Stewart in 1922,

A root hole, bears North,  $55\frac{1}{2}$  lks. dist., alongside of which is an uprooted and rotted oak, 24 ins. diam., with no marks visible.

A fir, 32 ins. diam., bears N.  $88\frac{1}{2}$ ° E., 106 lks. dist., with a healed blaze.

and bearing trees mkd. by George Wenderoth, Registered Land Surveyor No. 5, in 1963.

A black oak, 31 ins. diam., bears S. 83° E.,  $50\frac{1}{2}$  lks. dist., with scribe marks S35 CS BT visible on open blaze.

A white oak, 14 ins. diam., bears S.  $58\frac{1}{2}$ ° W., 94 lks. dist., with scribe marks 3 CS visible on open blaze.

A black oak, 20 ins. diam., bears N.  $80\frac{3}{4}$ ° W., 83 lks. dist., with scribe marks S27 CS BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground directly over the iron pipe, with brass cap mkd.

T 30 S R 5 W
S 27   S 26
S 34   S 35
1967

FD OK. 7/83  
W. ZUPPERT L.S. # 866  
M 9A-66

From this point, the SW cor. of the William P. Preston Donation Land Claim, No. 62, bears N. 28° 51' W., 3.48 chs. dist., perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, again perpetuated and recorded by George Wenderoth, Registered Land Surveyor No. 5, in 1953, monumented with an iron pipe, 1 in. diam., protruding 4 ins. above ground, firmly set, from which the original bearing tree:

A white oak, 29 ins. diam., bears N. 70° E., 50 lks. dist., with no marks visible on rotted blaze. This tree was remarked by Stewart in 1922 and scribe marks 62 C BT are visible on open double blaze alongside the rotted original blaze.

and a bearing tree mkd. by Stewart in 1922,