

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 30 S., R. 5 W.

CHAINS	
59.30	Wet ravine, drains S. 35° W.; desc. 150 ft. along W. slope changing to SW. slope.
63.35	Power and telephone line, bears N. 40° W. and S. 40° E.
65.90	Wire fence at NE. edge of open right of way, bears NW. and SE.
68.75	Canyon Creek, 35 lks. wide, course N. 50° W. from S. 35° E.; asc. 110 ft. over NE. slope.
71.30	Center of N. bound lanes of Interstate Highway No. 5, 50 lks. wide, bears NW. and SE. curving to S.
72.40	Center of S. bound lanes of Interstate Highway No. 5, 50 lks. wide, bears NW. and SE. curving to S.
75.50	Top of open cut bank, edge bears N. 30° W. curving to W. and S. 30° E. curving to S.; asc. 20 ft. over NE. slope along edge of timber.
76.40	The original 1854 Nathaniel Ford cor. of secs. 2, 3, 34, and 34, at record bearing and distance from the remaining original bearing tree <p data-bbox="456 1194 1377 1264" style="margin-left: 40px;">A fir, 30 ins.diam., bears S. 33° W., 38 lks. dist., with scribe marks S24 BT visible on opened blaze.</p> <p data-bbox="326 1291 829 1319">and a bearing tree of no record</p> <p data-bbox="456 1355 1377 1480" style="margin-left: 40px;">A fir, 27 ins.diam., bears N. 54° W., 60 lks. dist., with scribe marks S27 BT visible on opened blaze. A count of annual growth rings equals the age of the 1854 Ford survey.</p> <p data-bbox="326 1519 1401 1749">At the corner point set a concrete filled galvanized iron pipe, 30 ins. long, 1 in. diam., 24 ins. in the ground. In accordance with a memorandum from Chief, Division of Engineering, Washington, D. C. dated August 30, 1967, Survey procedure, Group 614, Oregon; this cor. is treated as an off line closing cor. and the line bet. secs. 34 and 35 is projected southerly through it to the township line as determined by William H. Byers in 1882.</p> <p data-bbox="326 1782 789 1810">Ascend 85 ft. over NE. slope.</p>
79.05	Wire fence at SW. edge of right of way, bears N. 30° W. and S. 30° E. enter timber.
80.50	Top of ascent, slopes E.; desc. 5 ft. along E. slope.
81.98	The cor. of secs. 34 and 35 only, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., protruding 4 ins. above ground, firmly set, with brass cap mkd. and witnessed as described in the field notes of the 1967 dependent resurvey of the N. bdy. of T. 31 S., R. 5 W., under Group 614, Oregon.
	Land, mountainous. Soil, rocky clay. Timber, fir, oak, madrone, maple, alder, cedar, dogwood, myrtle, cascara, and pine; undergrowth, poison oak, fern, salal, hazel, arrowwood, vine maple, Oregon grape, blackberry, wild rose, and reproduction.