

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 30 S., R. 5 W.

CHAINS

Remonumentation of a Certain Original Corner Point,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

(Restoring the 1854 survey by Nathaniel Ford)

The following field notes describe the remonumentation of a certain original corner point in T. 30 S., R. 5 W., as provided for by the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The cor. of secs. 28, 29, 32, and 33, perpetuated and recorded by J. H. Markham, Registered Engineer No. 2880, in 1949, monumented with an iron pipe, 3/4 in. diam., protruding 4 ins. above ground, firmly set, from which the remaining original bearing trees:

A sawed black oak stump, 28 ins. diam., bears N. 86° E.,
13 lks. dist., with portion of overgrowth remaining.
(Record, S. 89½° E., 11 lks. dist.)

A white oak, 33 ins. diam., bears S. 58° W., 76 lks. dist.,
with no evidence of original blaze visible. In 1949,
Markham remarked this tree and illegible scribe marks
are visible on open blaze. (Record, S. 55° W., 75 lks.
dist.)

A stump hole, bears N. 55° W., 54 lks. dist.

and a bearing tree mkd. by Markham in 1949.

A white oak, 18 ins. diam., bears N. 67½° W., 165 lks. dist.
with illegible scribe marks visible on open blaze.

and a bearing tree mkd. by J. W. Byron, Deputy County Surveyor, in
1963,

A sawed white oak stump, 9 ins. diam., bears S. 3¼° E.,
17 lks. dist., with scribe marks CS BT visible on
remaining portion of open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground
directly over the iron pipe, with brass cap mkd.

T 30 S R 5 W
S 29 | S 28
S 32 | S 33
1967

FD. OK 8/91
R. BROWN M113-68

GENERAL DESCRIPTION

Section 35 lies in a mountainous area southeast of Canyonville Oregon. The elevation ranges from about 800 feet above sea level to about 2,640 feet above sea level. The soil is a rocky clay with patches of loam in the creek bottoms. The predominant timber is fir, with a scattering of oak, madrone, cedar, alder, maple, dogwood, chinquapin, cascara, willow, pine, and myrtle. Undergrowth consists chiefly of poison oak, fern, salal, vine maple, hazel, arrowwood, Oregon grape, huckleberry, blackberry, nettle, ceanothus manzanita and reproductions.