

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 9 W.

CHAINS	
	A fir, 17 ins. diam., bears S. 15° E., 25 lks. dist., with healed double blaze.
	A fir, 17 ins. diam., bears S. 63° W., 15 lks. dist., with healed double blaze.
	A fir, 16 ins. diam., bears N. 37° W., 62 lks. dist., with healed double blaze.
	N. 0° 17' E., bet. secs. 15 and 16.
	Descend 150 ft. over broken NW. slope, across old logged area, through dense young timber.
18.50	Dirt road, 20 lks. wide, bears N. and S. 10° E.
22.80	Leave road, bears S. and N. 25° E.
25.80	Asphalt road, 25 lks. wide, bears N. 55° E. and S. 55° W.
40.24	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate distance, there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
	$\frac{1}{4}$ S 16 S 15 T 29 S R 9 W 1968
	from which
	A fir, 10 ins. diam., bears S. 57° E., 11 lks. dist., mkd. $\frac{1}{4}$ S15 BT.
	A fir, 7 ins. diam., bears N. 49° W., 15 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S16 BT.
	Descend 295 ft. over broken NW. slope.
62.10	Creek, 1 lk. wide, course W.; asc. 45 ft. over SW. slope.
66.20	Spur, slopes W.; desc. 380 ft. over NW. slope.
77.15	Creek, 15 lks. wide, course W.; asc. 200 ft. over S. slope.
81.67	The original closing cor. of secs. 15 and 16, monumentd with the original sandstone, 20 x 15 x 8 ins., loosely set 6 ins. in the ground, marked with 4 grooves on S. and 3 grooves on E. side.
	Ascend 10 ft. over S. slope.
81.93	Intersect the S. bdy. of sec. 10.
	True point for the closing cor. of secs. 15 and 16.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
	T 29 S R 9 W S 10 S 16 S 15 CC 1968
	from which