

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R 9 W.

CHAINS

78.82

The cor. of secs. 3, 4, 9, and 10, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1959, monumented with an iron post, 36 ins. long, $1\frac{1}{2}$ ins. diam., firmly set 24 ins. in the ground, with brass cap marked

COOS COUNTY DOUG. CO. SURVEYORS OFF.

T 29 S R 9 W

S 4 | S 3

S 9 | S 10

1959

from which the original bearing trees:

A sawed hemlock stump, 20 ins. diam., bears N. 85° E., 29 lks. dist., no marks visible on opened and rotted blaze. (Record, N. 80° E.)

A sawed fir stump, 62 ins. diam., bears S. 25° E., 48 lks. dist., with fragmentary scribe marks visible on weathered bark blaze.

A cedar, 18 ins. diam., bears S. 58° W., 26 lks. dist., with scribe marks 9S R9W visible on partially healed blaze. (Record, S. 60° W., 24 lks.)

A fir root crown, 80 ins. diam., bears N. 45° W., 6 lks. dist., no marks remaining.

and a bearing tree marked by Byron:

A hemlock, 21 ins. diam., bears N. 89° W., 64 lks. dist., with scribe marks T29S R9W S4 DCS BT visible on partially healed double blaze.

and new bearing trees:

A hemlock, 18 ins. diam., bears N. 18° E., 35 lks. dist., mkd. T29S R9W S3 BT.

A hemlock, 13 ins. diam., bears S. $37\frac{1}{2}^{\circ}$ E., 75 lks. dist., mkd. T29S R9W S10 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, madrone, alder, chinquapin, and willow; undergrowth, huckleberry, vine maple, young timber, salmonberry, thimbleberry, hazel, arrowwood, ceanothus, Oregon grape, salal, and fern.

From the cor. of secs. 20, 21, 28, and 29, monumented with an iron pipe, 30 ins. long, $\frac{3}{4}$ in. diam., firmly set 24 ins. in the ground, from which the original bearing trees:

A sawed cedar stump, 25 ins. diam., bears N. 65° E., 50 lks. dist., with scribe marks T29S R9W S21 BT visible on opened blaze.

A hemlock snag, 20 ins. diam., bears S. 64° E., 23 lks. dist., no marks on decayed face of blaze. (Record, S. 60° E.)

A hemlock snag, 30 ins. diam., bears S. 42° W., 71 lks. dist., with scribe marks 29S R9W S29 BT visible on opened blaze. (Record, S. 35° W.)