

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 9 W.

CHAINS

A sawed fir stump, 70 ins. diam., bears N. 17° W., 70 lks. dist., with healed blaze. (Record, N. 25° W., 66 lks.)

and bearing trees of which I have no record:

A hemlock, 20 ins. diam., bears S. 84° E., 35 lks. dist., with scribe marks S28 BT visible on open blaze.

A sawed fir stump, 60 ins. diam., bears S. 86° W., 36 lks. dist., with scribe marks S29 BT visible on open blaze.

at the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 29 S R 9 W
S 20 | S 21
S 29 | S 28
1968

from which new bearing trees:

A fir, 13 ins. diam., bears N. 30° E., 45 lks. dist., mkd. T29S R9W S21 BT.

A hemlock, 20 ins. diam., bears S. 85° W., 52 lks. dist., mkd. T29S R9W S29 BT.

A fir, 15 ins. diam., bears N. 29° W, 21 lks. dist., mkd. T29S R9W S20 BT.

Reset the iron pipe alongside iron post.

N. 0° 45' E., bet. secs. 20 and 21

Descend 20 ft. over NW. slope, through old logged area and dense young timber.

8.80 Creek, 2 lks. wide, course S. 80° W.; asc. 100 ft. over SW. slope.

24.30 Top of ascent , slopes W.; desc. 330 ft. over NW. slope.

33.00 Dirt road, 15 lks. wide, in curve, bears E. and S. 25° W.

40.27 The ¼ sec. cor. of secs. 20 and 21, determined at record bearing and distance from the remaining original bearing tree:

A root hole, bears S. 20° E., 24 lks. dist., with a down hemlock alongside, 20 ins. diam., with scribe marks ¼ S21 B visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass capmarked

¼
S 20 | S 21
T 29 S R 9 W
1968

from which new bearing trees:

A fir, 6 ins. diam., bears S. 18° E., 34 lks. dist., mkd. ¼ S21 BT.

A fir, 12 ins. diam., bears N. 1° W., 106 lks. dist., mkd. ¼ S20 BT.