

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 9 W.

CHAINS

The corner falls on the S. edge of a swamp, bears E. and W.

N. 0° 25' E., beginning new measurement.

Continue across swampy area.

- 1.00 N. edge of swamp, bears E. and W.; asc. 30 ft. over S. slope.
- 2.15 Spur, slopes W.; desc. 105 ft. over N. slope.
- 6.00 Creek, 4 lks. wide, course N. 35° W.; asc. 15 ft. over SW. slope.
- 7.90 Top of ascent, slopes W.; desc. 95 ft. over NW. slope.
- 13.60 Creek, 2 lks. wide, course N. 70° W.; asc. 65 ft. over SW. slope.
- 24.40 Spur, slopes NW.; desc. 260 ft. over N. slope.
- 33.35 Creek, 4 lks. wide, course N. 35° W.; asc. 30 ft. over SW. slope.
- 34.90 Point of spur, slopes W.; desc. 5 ft. over NW. slope.
- 36.10 Creek, 6 lks. wide, course SW.; asc. 80 ft. over SW. slope.
- 39.56 The cor. of secs. 16, 17, 20, and 21, monumented with the original sandstone, 16 x 14 x 9 ins., firmly set 12 in. in the ground, marked with 3 grooves on the S. and 4 grooves on the E. sides, from which the original bearing trees:

- A root hole bears N. 36° E., 24 lks. dist.
- A root hole bears S. 75° E., 29 lks. dist., with a down fir alongside, 14 ins. diam., with scribe marks 29S R9W S29 B visible on opened blaze. (Record, S. 40° E.)
- A root hole bears S. 55° W., 26 lks. dist., with a down fir alongside, 16 ins. diam., with fragmentary scribe marks visible on opened and rotted blaze.
- A fir root crown, 16 ins. diam., bears N. 45° W., 3 lks. dist., no marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 29 S R 9 W				
<table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;">S 16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> </table>	S 17	S 16	S 20	S 21
S 17	S 16			
S 20	S 21			
1968				

from which new bearing trees

- A fir, 12 ins. diam., bears N. 83° E., 17 lks. dist., mkd. T29S R9W S16 BT.
- A cedar, 7 ins. diam., bears S. 35° E., 9 lks. dist., mkd. T29S R9W S21 BT.
- A fir, 12 ins. diam., bears S. 85° W., 20 lks. dist., mkd. T29S R9W S20 BT.
- A fir, 10 ins. diam., bears N. 52° W., 9 lks. dist., mkd. T29S R9W S17 BT.