

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 9 W.

## CHAINS

Deposit the original corner stone alongside iron post.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, chinquapin, madrone, alder, yew, and willow; undergrowth, vine maple, hazel, huckleberry, arrowwood, salmonberry, thimbleberry, young timber, ceanothus, Oregon grape, salal, and fern.

From the cor. of secs. 15, 16, 21, and 22.

N. 89° 41' W., bet. secs. 16 and 21.

Descend 430 ft. over NW. slope, across old logged area, through dense young timber.

10.00 Asphalt road, 25 lks. wide, bears N. 30° W. and S. 30° E.

27.50 Creek, 2 lks. wide, course N.; asc. 170 ft. over NE. slope.

32.90 Top of ascent, slopes N.; desc. 65 ft. over NW. slope.

39.99 The  $\frac{1}{4}$  sec. cor. of secs. 16 and 21, determined at record bearing and distance from the original bearing trees:A hemlock snag, 20 ins. diam., bears N. 20° W., 34 lks. dist., with scribe marks  $\frac{1}{4}$  S16 BT visible on opened blaze.

A rotted hemlock stump, 22 ins. diam., bears S. 45° W., 58 lks. dist., no marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked
$$\frac{1}{4} \frac{S \ 16}{S \ 21}$$

T 29 S R 9 W  
1968

from which new bearing trees

A fir, 15 ins. diam., bears N. 50° W., 3 lks. dist., mkd.  $\frac{1}{4}$  S16 BT.A hemlock, 21 ins. diam., bears S. 54° W., 48 lks. dist., mkd.  $\frac{1}{4}$  S21 BT.

N. 89° 31' W., beginning new measurement.

Descend 500 ft. over general NW. slope.

36.00 Creek, 2 lks. wide, course S. 70° W.; asc. 35 ft. over SE. slope.

40.57 The cor. of secs. 16, 17, 20, and 21.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, chinquapin, alder, yew, and willow; undergrowth, young timber, vine maple, huckleberry, hazel, arrowwood, salmonberry, thimbleberry, ceanothus, Oregon grape, salal, and fern.