

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 9 W.

CHAINS

From the cor. of secs. 9 and 10 only.

S 89° 39' W., on the S. bdy. of sec. 9.

Descend 395 ft. over SW. slope, through heavy timber and dense undergrowth, along old blaze line.

27.80 Creek, 8 lks. wide, course S. 10° W.; asc. 85 ft. over SE. slope.

40.10 Point for the $\frac{1}{4}$ sec. cor. of sec. 9 only, at proportionate distance, there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 29 S R 9 W
<u> $\frac{1}{4}$ S 9</u>
1968

from which

A hemlock, 10 ins. diam., bears N. 24° E., 40 lks. dist., mkd. $\frac{1}{4}$ S9 BT.A fir, 6 ins. diam., bears N. 38° W., 19 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

Ascend 15 ft. over SE. slope.

41.30 Top of ascent, slopes S.; desc. 140 ft. over SW. slope.

49.65 Creek, 2 lks. wide, course S. 15° E.; asc. 110 ft. over SE. slope.

52.80 Spur, slopes S. 30° W.; desc. 180 ft. over SW. slope.

59.10 Creek, 4 lks. wide, course S. 15° E.; asc. 410 ft. over SE. slope.

78.30 Top of ascent, slopes S.; desc. 40 ft. over SW. slope.

79.52 The cor. of secs. 8, 9, 16, and 17, determined from the original bearing trees:

A fir snag, 64 ins. diam., bears S. 73° E., 33 lks. dist., with fragmentary scribe marks visible on weathered bark blaze.

A cedar snag, 58 ins. diam., bears S. 14° W., 45 lks. dist. with scribe marks S17 visible on opened blaze. (Record, 41 lks.)

A cedar snag, 33 ins. diam., bears N. 50° W., 9 lks. dist., with scribe marks 29 R9W visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 29 S R 9 W
<u> S 8 S 9</u>
S 17 S 16
1968

from which new bearing trees