

Dependent Resurvey, Portion of the W. Bdy., T. 22 S. R. 7 W.

CHAINS

and a tree mkd. by Milo Godfrey, Deputy County Surveyor, in 1962.

A white fir, 15 ins. diam., bears N. 59° W., 311 lks. dist.,
with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground,
and in a mound of stone, 3 ft. base, to top, with brass cap marked

T 22 S
R 8 W R 7 W
<u>S 12 S 7</u>
S 13 S 18
1968

Deposit the iron rod and set a 6 ft. steel fence post
alongside the iron post.

N. 0° 02' W., bet. secs. 7 and 12, marking the true line.

Ascend 165 ft. over general S. slope, across pasture land.

19.93 Point for the S 1/16 sec. cor. of secs. 7 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, and in a mound of stone, 3 ft. base, to top, with brass
cap marked

S 1/16
<u>S 12 S 7</u>
1968

from which

A white oak, 24 ins. diam., bears N. 19° W., 134 lks. dist.,
mkd. S 1/16 S12 BT.

No other suitable trees available within limits.

Set a 6 ft. steel fence post alongside the iron post.

Ascend 16 ft. over S. slope.

21.65 Ravine, drains S. 20° W.; asc. 85 ft. over S. slope.

35.07 Intersect the N. bdy. of Donation Land Claims No. 40 and 44.

Point for the closing cor. of secs. 7 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, and in a mound of stone, 3 ft. base, to top, with brass
cap marked

T 22 S
R 8 W R 7 W
CC
<u>S 12 S 7</u>
C 40 C 44
1968

No suitable trees available within limits.

Set a 6 ft. steel fence post alongside the iron post.