

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the W. Bdy., T. 22 S., R. 7 W.

## CHAINS

From this point the NE. cor. of Claim 44, bears N. 89° 58' E., 7.49 chs. dist., hereinafter described.

Ascend 65 ft. over S. slope.

39.86

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1929, when the original bearing trees were existent; subsequently remonumented by Milo E. Godfrey, Deputy County Surveyor, in 1962, with an iron post,  $1\frac{1}{2}$  ins. diam., projecting 12 ins. above ground, firmly set, with brass cap marked

## COUNTY SURVEYORS OFFICE

T 22 S  
 $\frac{1}{4}$  S 12 | S 7  
 R 8 W | R 7 W  
 1962

from which new bearing trees

A fir, 7 ins. diam., bears N. 83° E., 397 lks. dist.,  
 mkd.  $\frac{1}{4}$  S7 BT.

A fir, 6 ins. diam., bears N. 60 $\frac{1}{4}$ ° W., 425 lks. dist.,  
 mkd.  $\frac{1}{4}$  S12 BT.

Set a 6 ft. steel fence post alongside the iron post.

N. 10° 12' E., beginning new measurement.

Ascend 75 ft. over SW. slope.

8.50

Spur, slopes S. 80° W.; desc. 85 ft. over NW. slope.

15.30

Creek, 1 lk. wide, course N. 70° W.; asc. 140 ft. over SW slope.

36.80

Ridge, bears N. 40° W. and S. 40° E.; desc. 125 ft. over NE. slope.

39.51

The cor. of secs. 1, 6, 7, and 12, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1929, monumented with a sandstone, 30 x 15 x 8 ins. firmly set 18 ins. in the ground, marked X on the top, 1 on NW., 6 on NE., 7 on SE., and 12 CS on SW. face, from which the original bearing trees:

A fir, 45 ins. diam., bears S. 48° E., 42 lks. dist., with  
 scribe marks T22S R7W S7 CS BT visible on the bark.  
 (Record bearing S. 42° E.)

A fir snag, 63 ins. diam., bears S. 42° W., 30 lks. dist.,  
 with scribe marks S12 T22S R3W visible on the bark.  
 (Record dist., 35 lks.)

A fir, 38 ins. diam., bears N. 5° W., 24 lks. dist., with  
 healed blaze. (Record bearing N. 15° W.)

and a bearing tree marked by Milo E. Godfrey, Deputy County Surveyor, in 1962

A hemlock, 16 ins. diam., bears N. 40° E., 75 lks. dist.,  
 with fragmentary scribe marks visible on open double  
 blaze.

At the corner point