

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 7 W.

## CHAINS

- N. 88° 24' W., bet. secs. 6 and 7.
- Ascend 335 ft. over SE. slope, through heavy timber and dense undergrowth.
- 17.90 Ridge, bears NE. and SW.; desc. 100 ft. over NW. slope.
- 23.20 Ravine, drains N.; asc. 125 ft. over NE. slope.
- 25.70 Spur, slopes N.; desc. 165 ft. over NW. slope.
- 30.80 Ravine, drains N. 10° E.; asc. 250 ft. over NE. slope.
- 36.96 The  $\frac{1}{4}$  sec. cor. of secs. 6 and 7, at proportionate distance, reestablished and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1963, monumented with a T shaped iron rod, 36 ins. long, firmly set 30 ins. in the ground, from which the Haines bearing tree
- A fir, 8 ins.diam., bears S. 21° E., 54 lks. dist., with fragmentary scribe marks visible on open double blaze.
- At the corner point
- Set an ironpost, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked
- $$\frac{1}{4} \frac{S 6}{S 7}$$
- T 22 S R 7 W  
1968
- from which a new bearing tree
- A fir, 7 ins. diam., bears N. 16° W., 50 lks. dist., mkd.  $\frac{1}{4}$  S6 BT.
- Deposit the iron rod alongside the iron post.
- 
- N. 88° 24' W., beginning new measurement.
- Ascend 65 ft. over NE. slope.
- 7.00 Ridge, bears N. 80° W. and S. 80° E.; desc. 40 ft. along S. slope.
- 13.30 Same ridge, bears NE. and SW.; desc. 140 ft. over NW. slope.
- 18.48 Point for the W 1/16 sec. cor. of secs. 6 and 7.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked
- $$W 1/16 \frac{S 6}{S 7}$$
- 1968
- from which
- A fir, 25 ins. diam., bears N. 41° W., 57 $\frac{1}{2}$  lks. dist., mkd. W 1/16 S6 BT.
- A fir, 4 ins. diam., bears S. 23° W., 28 lks. dist., mkd. W 1/16 S7 BT.
- Descend 120 ft. over NW. slope.