

Dependent Resurvey, Portion Subdivisional Lines, T. 22 S., R. 7 W.

CHAINS

- 21.70 Ravine, drains N. 40° W.; desc. 85 ft. along N. slope.
- 26.20 Ravine, drains N. 30° W.; asc. 40 ft. over NE. slope.
- 29.30 Spur, slopes N. 15° W.; desc. 55 ft. over NW. slope.
- 31.20 Ravine, drains N. 15° W.; asc. 105 ft. over NE. slope.
- 36.96 The cor. of secs. 1, 6, 7, and 12.

Land, mountainous.
 Soil, sandy clay loam.
 Timber, fir, hemlock, white fir, cedar, maple, chinquapin, alder, yew, dogwood, madrone, cascar, and wild cherry; undergrowth, hazel, arrowwood, huckleberry, vine maple, salmonberry, thimbleberry, ceanothus, poison oak, Scotch broom, manzanita, Oregon grape, salal, and fern.

Dependent Resurvey of a Portion of the Boundaries of
 Donation Land Claim No. 43, T. 22 S., R. 7 W.,
 Willamette Meridian, Oregon

(Restoring the 1856 survey by Dennis Hathorn)

From the SE. cor. of Donation Land Claim No. 43, in section 18, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1967, monumented with an iron rod, 30 ins. long, $\frac{1}{2}$ in. diam., firmly set 24 ins. in the ground, from which the original bearing trees:

- A sawed fir stump, 38 ins. diam., bears N. 10° E., 58 lks. dist., with scribe marks 22S 7W visible on opened blaze.
- A sawed fir stump, 45 ins. diam., bears N. 80° W., 52 lks. dist., with healed blaze.

and trees marked and recorded by Vernon Tracey, Deputy County Surveyor, in 1967

- A fir, 11 ins. diam., bears S. 80° E., 28 lks. dist., with fragmentary scribe marks visible on open blaze.
- A fir, 12 ins. diam., bears S. 3° W., 32 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 7 W

 C 43 | S 18
 1968

Deposit the iron rod alongside the iron post.