

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion Bdrs. Claim No. 43, T. 22 S., R. 7 W.

CHAINS

S. 89° 58' W., along the S. bdy. of Claim No. 43.

Thence across rolling open pasture land.

49.32

Point for the SW. cor. of Claim No. 43, determined by the method of broken boundaries; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 7 W

S 18 | C 43
1968

from which

A fir, 15 ins. diam., bears N. 34° E., 59 lks. dist.,
mkd. T22S R7W C43 BT.A fir, 28 ins. diam., bears S. 17° E., 43 lks. dist.,
mkd. T22S R7W S18 BT.

N. 0° 16' W., along the W. bdy. of Claim No. 43.

Descend 70 ft. over NW. slope, through scattered timber and dense undergrowth.

7.00

Creek, 1 lk. wide, course S. 80° W.; asc. 150 ft. over SW. slope.

25.30

Spur, slopes W.; desc. 195 ft. over NW. slope.

31.75

Hart Creek, 4 lks. wide, course S. 75° W.; asc. 360 ft. over SW. slope.

59.35

Intersect the line bet. secs. 7 and 18.

Point for the closing cor. of secs. 7 and 18, herein-before described.

From this point the W 1/16 sec. cor. of secs. 7 and 18, bears S 89° 59' W., 2.76 chs. dist., hereinbefore described.

Ascend 20 ft. over SW. slope.

61.30

Creek, 1 lk. wide, course S. 5° W.; asc. 115 ft. over S. slope.

70.70

Point for the NW. cor. of Claim No. 43, determined by the method of broken boundaries; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T 22 S R 7 W

S 7 | C 43
1968