

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey Birs. Claims No. 40 and 44, T. 22 S., R. 7 & 8 W.

CHAINS

A fir, 10 ins. diam., bears N. 5° E., 276 lks. dist., with healed double blaze.

A fir, 33 ins. diam., bears S. 1° W., 394 lks. dist., with healed double blaze.

South, along the E. bdy. of Claim No. 44.

Descend 115 ft. over SW. slope, through pasture land.

15.20 Intersect the E. and W. center line of the SW. $\frac{1}{4}$ of sec. 7.

Point for the closing cor. of the E. and W. center line of the SW. $\frac{1}{4}$ of sec. 7 with the E. bdy. of Claim No. 44, hereinafter described.

From this point the S $\frac{1}{16}$ sec. cor. of secs. 7 and 12, T. 22 S., Rs. 7 and 8 W., bears N. 89° 30' W., 7.46 chs. dist., hereinbefore described.

Descend 215 ft. over SW. slope.

35.09 Intersect line bet. secs. 7 and 18, N. 89° 59' E., 7.47 chs. from cor. secs. 7, 12, 13, and 18 on W. bdy. of Tp.

41.29 Point for the SE. cor. of Claim No. 44, determined by the method of broken boundaries; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked

T 22 S R 7 W

C 44 | S 18
1968

from which

A fir, 13 ins. diam., bears N. 88° E., 631 lks. dist., mkd. T22S R7W S18 BT.

Set a 6 ft. steel fence post alongside the iron post.

S. 89° 57' W., along the S. bdy. of Claim No. 44, T. 22 S., R. 7 W. and 40, T. 22 S., R. 8 W.

Thence over rolling open land.

38.75 Point for the SW. cor. of Claim No. 40, T. 22 S., R. 8 W., determined by the method of broken boundaries; there is no remaining evidence of the original corner; no permanent monument established.

North, along the W. bdy. of Claim No. 40.

Thence over rolling open land.

41.26 The NW. cor. of Claim No. 40, occupied by the original corner tree; a rotted white oak stump, 20 ins. diam., with old axe marks visible on W. face, from which the original bearing trees: