

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7, T. 22 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

C ¼ S 7
1968

from which

A hemlock, 10 ins. diam., bears S. 33° E., 46 lks. dist., mkd. C ¼ S 7 BT.

A hemlock, 6 ins. diam., bears N. 62° W., 34 lks. dist., mkd. C ¼ S 7 BT.

Ascend 45 ft. over NE. slope.

40.30 Spur, slopes E.; desc. 70 ft. over SE. slope.

43.00 Creek, 1 lk. wide, course S. 70° E.; asc. 80 ft. over NE. slope.

45.35 Spur, slopes E.; desc. 120 ft. over SE. slope.

51.80 Creek, 2 lks. wide, course N. 65° E.; asc. 380 ft. over NW. slope.

58.35 Point for the center S 1/16 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap marked

*SEE C.S. 63/138
FOR REV. REPORT
8/7/92*

C
S 1/16 | S 7
C
1968

*SEE C.S. 63/127
FOR REV. REPORT
11/17/90*

from which

A fir, 28 ins. diam., bears N. 41° E., 10 lks. dist., mkd. CS 1/16 S 7 BT.

A fir, 34 ins. diam., bears S. 41° W., 39 lks. dist., mkd. CS 1/16 S 7 BT.

Ascend 160 ft. over NW slope.

63.20 Ridge, bears N. 80° W. and S. 80° E.; desc. 40 ft. over SW. slope.

66.49 Intersect the N. bdy. of Donation Land Claim No. 43.

Point for the closing cor. of the N. and S. center line of sec. 7 with the N. bdy. of Claim No. 43.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ind. in the ground, with brass cap marked

C
CC | S 7
C
C 43
1968

from which

A fir, 5 ins. diam., bears N. 38° E., 53 lks. dist., mkd. T22S R7W S7 CC BT.

A fir, 5 ins. diam., bears N. 23° W., 105 lks. dist., mkd. T22S R7W S7 CC BT.