

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7, T. 22 S., R. 7 W.

| CHAINS |   |
|--------|---|
|        | <p>From this point the NE. cor. of Claim No. 43 bears S. 89° 58' E., 13.61 chs. dist., hereinbefore described.</p> <p>Descend 105 ft. over SW. slope.</p>   |
| 69.00  | Enter pasture land, edge bears N. 70° W. and S. 70° E.  |
| 77.90  | The $\frac{1}{4}$ sec. cor. of secs. 7 and 18.  |
| <hr/>  |   |
|        | <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 8.</p> <p>N. 88° 59' W., on the E. and W. center line of sec. 7.</p> <p>Descend 255 ft. over SW. slope, through scattered timber and dense undergrowth.</p> |
| 11.65  | Creek, 1 lk. wide, course S. 30° W.; asc. 400 ft. over SE. slope.   |
| 26.80  | Spur, slopes S. 20° W.; desc. 300 ft. over SW. slope.   |
| 37.10  | Creek, 4 lks. wide, course S. 35° E.; asc. 95 ft. over NE. slope.   |
| 38.54  | The center $\frac{1}{4}$ sec. cor. of sec. 7.   |
|        | Ascend 530 ft. over general E. slope.   |
| 59.19  | Point for the center W 1/16 sec. cor. for the NW $\frac{1}{4}$ of sec. 7, as based on the Byars plat of 1872.   |
|        | Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap marked   |
|        | $C \frac{W \ 1/16 \ S \ 7}{1968} C$   |
|        | from which  |
|        | A fir, 10 ins. diam., bears N. 66° E., 12 lks. dist., mkd. CW 1/16 S7 BT.   |
|        | A fir, 12 ins. diam., bears N. 73° W., 15 lks. dist., mkd. CW 1/16 S7 BT.   |
|        | Ascend 1 ft. over SE. slope.  |
| 60.04  | Point for the center W 1/16 sec. cor. for the SW $\frac{1}{4}$ of sec. 7, as based on the Gordon and Gardner plat of 1856.  |
|        | Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked  |
|        | $C \frac{W \ 1/16 \ S \ 7}{1968} C$   |
|        | from which  |
|        | A fir, 7 ins. diam., bears S. 22 $\frac{1}{2}$ ° E., 71 lks. dist., mkd. CW 1/16 S7 BT.   |
|        | A fir, 12 ins. diam., bears S. 6° W., 17 lks. dist., mkd. CW 1/16 S7 BT.  |
|        | Ascend 50 ft. over SE. slope.   |