

## County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 7, T. 22 S., R. 7 W.

## CHAINS

66.00	Ridge, bears N. and S.; desc. 110 ft. over SW. slope.
70.00	Enter pasture land, edge bears N. and S.
79.84	The $\frac{1}{4}$ sec. cor. of secs. 7 and 12.
<hr/>	
	From the W $\frac{1}{16}$ sec. cor. of secs. 7 and 13.
	N. $1^{\circ} 57'$ E., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 7.
	Ascend 180 ft. over SE. slope, across pasture land.
18.20	Enter scattered timber and dense undergrowth, edge bears N. $60^{\circ}$ W. and S. $60^{\circ}$ E.
19.77	Point for the SW $\frac{1}{16}$ sec. cor. of sec. 7, at intersection with the E. and W. center line of the SW $\frac{1}{4}$ .
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked
	SW $\frac{1}{16}$ S 7 1968
	<i>SEE C.S. 63/127 for CORNER REPORT # 11/17/90</i>
	from which
	A fir, 15 ins. diam., bears N. $46^{\circ}$ W., 72 lks. dist., mkd. SW $\frac{1}{16}$ S7 BT.
	A fir, 12 ins. diam., bears S. $50^{\circ}$ E., $11\frac{1}{2}$ lks. dist., mkd. SW $\frac{1}{16}$ S7 BT.
	Ascend 2 ft. over S. slope.
19.90	Ridge, bears N. $50^{\circ}$ W. and S. $50^{\circ}$ E.; desc. 65 ft. over NE. slope.
27.00	Creek, 1 lk. wide, course S. $60^{\circ}$ E.; asc. 125 ft. over SE. slope.
39.49	The center W $\frac{1}{16}$ sec. cor. for the SW $\frac{1}{4}$ of sec. 7.
<hr/>	
	From the center S $\frac{1}{16}$ sec. cor. of sec. 7.
	N. $89^{\circ} 30'$ W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 7.
	Descend 70 ft. over NW. slope, through scattered timber and dense undergrowth.
2.40	Ravine, drains N. $20^{\circ}$ E.; asc. 80 ft. over NE. slope.
6.20	Spur, slopes N.; desc. 65 ft. over NW. slope.
8.90	Ravine, drains N. $20^{\circ}$ E.; asc. 195 ft. over NE. slope.
19.10	Ridge, bears NW. and SE.; desc. 5 ft. over SW. slope.
20.78	The SW $\frac{1}{16}$ sec. cor. of sec. 7.
	Descend 90 ft. over SW. slope.