

Dependent Resurvey, 5th Stan. Par. S., N. Bdy., T. 23 S., R. 8 W.

CHAINS

Ascend 5 ft. ~~over~~ NE. slope, through heavy timber and dense undergrowth.

3.30

The cor. of secs. 34 and 35 only, T. 22 S., R. 8 W., determined at record bearing and distance from the original bearing trees

A fir, 65 ins. diam., bears N. 53° E., 128 lks. dist., with healed blaze.

A maple, 25 ins. diam., bears N. 33° W., 48 lks. dist., with no marks remaining on rotted blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

*FWO OK 9/72
R. DOLAN MHS-68*

T 22 S R 8 W
S 34 | S 35
T 23 S R 8 W
S 3
1968

from which

A fir, 16 ins. diam., bears N. 34° W., 179 lks. dist., mkd. T22S R8W S34 BT.

Corner is located at top of ascent, slopes N.

N. 89° 31' W., beginning new measurement.

Descend 40 ft. over NW slope.

9.75

Bottom of descent, slopes N.; asc. 230 ft. over general NE. slope.

29.00

Spur, slopes NW.; desc. 185 ft. over W. slope.

36.70

Record distance for the standard ¼ sec. cor. of sec. 3 only, there is no remaining evidence of the original corner. This corner is superseded by the following corner based on the 1894 Whipple survey.

36.82

Point for the ¼ sec. cor. of sec. 3 only, at midpoint longitudinally on the N. bdy. of the section.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

¼ S 3
T 23 S R 8 W
1967

from which

A white fir, 13 ins. diam., bears S. 46° E., 28 lks. dist., mkd. ¼ S3 BT.

A fir, 18 ins. diam., bears S. 41° W., 28 lks. dist., mkd. ¼ S3 BT.

Descend 140 ft. over NW. slope.

40.00

Record distance for the ¼ sec. cor. of sec. 34 only, T. 22 S. R. 8 W.; there is no remaining evidence of the original corner.