

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, 5th Stan, Par. S., N. Bdy., T. 23 S., R 8 W.

## CHAINS

- 46.00 Leave timber, enter pasture, edge bears NE. and SW.
- 54.20 Heddin Creek, 6 lks. wide, course N. 10° E.; asc. 40 ft. over SE. slope.
- 56.88 Point for the W 1/16 sec. cor. of sec. 3 only.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked
- W 1/16 S 3  
1967
- from which
- A white oak, 6 ins. diam., bears S. 83° E., 42 lks. dist., mkd. W 1/16 S3 BT.
- A white oak, 9 ins. diam., bears S. 63° W., 31 lks. dist., mkd. W 1/16 S3 BT.
- Ascend 45 ft. over SE. slope.
- 62.00 Top of ascent, slopes S.; desc. 40 ft. over SW. slope.
- 64.50 Ravine, drains SE.; asc. 210 ft. over E. slope.
- 71.90 Top of ascent, slopes S.; desc. 5 ft. over SW. slope.
- 76.34 The standard cor. of secs. 3 and 4, determined at record bearing and distance from the original bearing trees
- A sawed fir stump, 40 ins. diam., bears S. 44° E., 225 lks. dist., with fragmentary scribe marks visible on opened blaze. (This tree was also used as the SE. bearing tree for the closing cor. of secs. 3 and 4 established by Whipple in 1894.)
- A rotted fir crown, size indeterminate, bears S. 29° W., 180 lks. dist., no marks remaining. (This tree was also used as the SW. bearing tree for the closing cor. of secs. 3 and 4 established by Whipple in 1894.)
- This corner now becomes an angle point on line.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap marked
- AP  
S 3  
T 23 S R 8 W  
1967
- from which
- A white oak, 12 ins. diam., bears S. 59° E., 183 lks. dist., mkd. AP S3 BT.
- A white oak, 18 ins. diam., bears S. 28° E., 228 lks. dist., mkd. AP S3 BT.
- 
- N. 87° 42' W., beginning new measurement.
- Descend 10 ft. over SW. slope.