

# 14432 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 8 W.


CHAINS

46.10 Leave pasture, enter oak timber and dense undergrowth, edge bears NW. and SE.

63.97 Left bank of Umpqua River, course N. 75° W.; bank is 16 ft. high.

Point selected for the witness cor. to the meander cor. of sections 11 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked



from which

A maple, 18 ins. diam., bears S. 30° E., 61 lks. dist., mkd. T23S R8W S12 WC MC BT.

A white oak, 28 ins. diam., bears S. 80° W., 157 lks. dist., mkd. T23S R8W S11 WC MC BT.

Descend 16 ft. over N. slope.

64.70 The original meander cor. of secs. 11 and 12, determined at record bearing and distance from the original bearing trees

A sawed white oak stump, 34 ins. diam., bears S. 29° E., 160 lks. dist., with no marks visible on opened and rotted blaze.

A sawed white oak stump, 25 ins. diam., bears S. 4° W., 255 lks. dist., with scribe marks BT visible on opened blaze.

and bearing trees mkd. by Arnold G. Gibson, Registered Surveyor No. 359, in 1957

A maple, 35 ins. diam., bears S. 44° W., 56 lks. dist., with healed blaze.

A myrtle, 22 ins. diam., bears N. 53° W., 120 lks. dist., with scribe marks 11 MC BT visible on open blaze.

The corner point falls below high water line; no permanent monument established.

N. 1° 00' E., beginning new measurement.

Descend 2 ft. across Umpqua River.

6.35 Right bank of Umpqua River bears N. 70° W. and S. 70° E.; asc. 35 ft. over S. slope, through oak timber and dense undergrowth.

7.97 Record distance for the meander cor. of secs. 11 and 12, on the right bank of the Umpqua River; there is no remaining evidence of the original corner.

10.35 Woven wire fence, bears E. and W. turning NW.; enter Dwight L. Phipps Forest Nursery (Oregon State).