

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 8 W.

CHAINS

15.04

The cor. of secs. 1, 2, 11, and 12, determined at record bearing and distance from the only remaining original bearing tree

A white oak, 38 ins. diam., bears S. 7° E., 490 lks. dist., with no marks visible on opened and rotted blaze.

and bearing trees mkd. by Arnold G. Gibson, Registered Surveyor No. 359, in 1957

A white oak, 25 ins. diam., bears S. 0¼° E., 477 lks. dist., with scribe mark T visible on open blaze.

A white oak, 23 ins. diam., bears S. 53° W., 500 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 76 ins. in the ground, with top 48 ins. below the surface of field, with brass cap marked

T 23 S R 8 W
S 2 | S 1
S 11 | S 12
1967

Land, S. half mile; mountainous, N. half mile; river bottom
Soil, sandy clay loam.

Timber, fir, cedar, hemlock, white fir, maple, myrtle, oak, madrone, chinquapin, alder, and willow; undergrowth, vine maple, arrowwood, salmonberry, hazel, thimbleberry, ceanothus, blackberry, poison oak, Oregon grape, salal, and fern.

The cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by Vernon Tracey, Deputy County Surveyor, in 1967, monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked

COUNTY SURVEYORS OFFICE
T 23 S
S 10 | S 11
S 15 | S 14
R 8 W
1967

from which the original bearing trees

A fir, 45 ins. diam., bears N. 5° E., 45 lks. dist., with healed blaze.

A root hole, bears S. 30° E., 79 lks. dist., along side of which is a down fir, 36 ins. diam., with no marks visible.

A root hole, bears N. 24° W., 30 lks. dist., alongside of which is a down white fir, 14 ins. diam., with no marks visible on opened and rotted blaze.

and bearing trees marked by Tracey

A chinquapin, 12 ins. diam., bears S. 16° E., 17 lks. dist., with scribe marks T23S R8W S14 CS BT visible on open double blaze.