

Dependent Resurvey, Portion of subdivisional Lines, T. 23 S., R. 8 W.

CHAINS

A chinquapin, 14 ins. diam., bears S. 73° W., 58 lks. dist., with scribe marks T23S R8W S15 CS BT visible on open double blaze.

A fir, 8 ins. diam., bears N. 66° W., 62 lks. dist., with scribe marks T23S R8W S10 CS BT visible on open double blaze.

S. 89° 57' E. bet. secs. 11 and 14.

Ascend 160 ft. over NW. slope, through heavy timber and dense undergrowth.

4.65 Spur, slopes N.; desc. 555 ft. over NE. slope.

19.83 Point for the W 1/16 sec. cor. of secs. 11 and 14.

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground with brass cap marked

W 1/16  $\frac{S\ 11}{S\ 14}$   
1967

from which

A cedar, 18 ins. diam., bears N. 28° E., 19 lks. dist., mkd. W 1/16 S11 BT.

A fir, 18 ins. diam., bears S. 11° W., 65 lks. dist., mkd. W 1/16 S 14 BT.

Descend 25 ft. over NE. slope.

21.05 Creek, 2 lks. wide, course N.; asc. 15 ft. over NW. slope.

21.30 Point of spur, slopes N.; desc. 15 ft. over E. slope.

21.55 Ravine, drains N. 25° W.; asc. 350 ft. over broken NW. slope.

39.66 Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

¼  $\frac{S\ 11}{S\ 14}$   
T 23 S R 8 W  
1967

from which

A fir, 16 ins. diam., bears N. 84° E., 93 lks. dist., mkd. ¼ S11 BT.

A fir, 36 ins. diam., bears S. 86° W., 116 lks. dist., mkd. ¼ S14 BT.

Ascend 225 ft. over NW. slope.

46.80 Spur ridge, bears N. and S.; desc. 495 ft. over general E. slope.