

Dependent Resurvey, ~~Portion~~ of Subdivisional Lines, T. 23 S., R. 8 W.

CHAINS

from which the original bearing trees

A white fir, 33 ins. diam., bears N. 32° E., 75 lks. dist., with no marks visible on opened and rotted blaze.

A fir, 60 ins. diam., bears S. 53° W., 68 lks. dist., with healed blaze.

A fir, 32 ins. diam., bears N. 68° W., 22 lks. dist., with healed blaze.

and bearing trees marked by Byron

A fir, 12 ins. diam., bears N. 76° W., 55 lks. dist., with healed double blaze.

A fir, 8 ins. diam., bears S. 74° W., 64 lks. dist., with healed double blaze.

Add marks BLM 1967 to brass cap.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, white fir, cedar, maple, myrtle, chinquapin, alder, and willow; undergrowth, vine maple, arrowwood, hazel, huckleberry, salmonberry, blackberry, poison oak, Oregon grape, salal, and fern.

N. 0° 21' E., along the E. bdy. of sec. 3.

Descend 95 ft. over N. slope, through heavy timber and dense undergrowth.

1.66

The closing cor. of secs. 2 and 11, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1959, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap marked

COUNTY SURVEYORS OFFICE

CC

S 3 | S 2
 | S 11

T 23 S | R 8 W

1959

from which the remaining original bearing tree

A fir, 40 ins. diam., bears S. 4° E., 69 lks. dist., with healed blaze.

and bearing trees marked by Byron

A fir, 18 ins. diam., bears N. 26° E., 66 lks. dist., with healed double blaze.

A fir, 10 ins. diam., bears S. 30° E., 23 lks. dist., with healed double blaze.

The original corner stone is alongside the iron post; a sandstone 14 x 12 x 6 ins., firmly set, projecting 8 ins. above ground, marked with 2 grooves and CC on E. face.

Descend 120 ft. over NE. slope.

5.25

Ravine, drains E.; asc. 195 ft. over SE. slope.