

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 8 W.

CHAINS

9.70 Woven wire fence, bears N. 65° W. and S. 65° E.; desc. 25 ft. over SW. slope, through heavy timber and dense undergrowth.

14.80 Right bank of Umpqua River, course N. 70° W.; desc. 15 ft. over bank and across river.

39.77 Point for the 1/4 sec. cor. of ~~secs. 2 and 11~~, at proportionate distance; falls in river. No permanent monument established.

*SHOULD BE FOR 11 ONLY FOR  
PTED BOUNDARY  
21.8. 1/2 sec. 11*

42.40 Left bank of Umpqua River, bears N. 50° W. and S. 70° E.; asc. 20 ft. over NE. slope.

45.36 Intersect the W. bdy. of Donation Land Claim No. 40, and point for the closing corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap marked

T 23 S R 8 W  
CC  $\frac{S 2}{S 11}$  C 40  
1967

from which

A fir, 40 ins. diam., bears N. 21° W., 21 lks. dist., mkd. T23S R8W S2 CC BT.

A fir, 35 ins. diam., bears S. 64° W., 46 lks. dist., mkd. T23S R8W S11 CC BT.

From this point the witness cor. for the NW. cor. of Claim 40, bears N. 0° 12' W., 0.33 chs. dist., hereinafter described.

From this same point, a locally established point of which I have no record, bears N. 10° 09' W., 0.135 chs. dist., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 4 ins. above ground,

*N 11-2'*

from which

A white fir snag, 23 ins. diam., bears N. 30° E., 20 1/2 lks. dist., with scribe marks S2 CS BT visible on open double blaze.

A myrtle, 10 ins. diam., bears S. 70° E., 25 lks. dist., with fragmentary scribe marks visible on open double blaze.

Corner is located at top of ascent, slopes N.; desc. 45 ft. over NW. slope.

48.15 Creek, 6 lks. wide, course N.; asc. 455 ft. over general E. slope.

51.00 Mehl Creek Road, 30 lks. wide, bears N. 20° W. and S. 20° E.

51.47 From this point a locally established point, of which I have no record, bears North, 0.16 chs. dist., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 4 ins. above ground,

from which

A fir, 17 ins. diam., bears S. 62° W., 21 lks. dist., with scribe marks CS visible on opened blaze.

63.01 From this point a locally established point, of which I have no record, bears North, 0.15 chs. dist., monumented with an iron rod, 1/2 in. diam., firmly set, projecting 10 ins. above ground.

from which