

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 8 W.

CHAINS	
6.00	Spur, slopes N.; desc. 15 ft. over NW. slope.
7.10	Ravine, drains N.; asc. 270 ft. over NE. slope.
12.55	Ridge, bears NW. and SE.; desc. 105 ft. over SW. slope.
23.60	Ravine, drains S.; asc. 260 ft. over SE. slope.
35.00	Top of ascent, slopes S.; desc. 35 ft. over SW. slope.
39.75	The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, perpetuated and recorded by Vernon Tracey, Deputy County Surveyor, in 1967, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap marked
	COUNTY SURVEYORS OFFICE T 23 S $\frac{1}{4}$ S 3 S 10 R 8 W 1967
	from which the original bearing trees
	A fir, 28 ins. diam., bears N. $32^\circ$ W., 32 lks. dist., with fragmentary scribe marks visible on opened blaze.
	A root hole, bears S. $70^\circ$ W., 35 lks. dist., alongside of which is a down fir, 52 ins. diam., with healed blaze.
	and bearing trees marked by Tracey
	A chinquapin, 7 ins. diam., bears N. $60^\circ$ E., 22 lks. dist., with scribe marks $\frac{1}{4}$ S3 CS BT visible on open double blaze.
	A white fir, 8 ins. diam., bears S. $47^\circ$ W., 54 lks. dist., with scribe marks $\frac{1}{4}$ S10 CS BT visible on open double blaze.
	Add marks BLM 1967 to brasscap.
	Corner falls at bottom of descent, slopes S.
	N. $89^\circ$ $38'$ W., beginning new measurement.
	Ascend 255 ft. over SE. slope.
8.35	Ridge, bears NE. and SW.; desc. 175 ft. over general W. slope.
19.75	Spur, slopes NW.; desc. 405 ft. over W. slope.
28.60	Ravine, drains N. $25^\circ$ W.; asc. 10 ft. over NE. slope.
35.10	Spur, slopes NW.; desc. 170 ft. over W. slope.
40.52	The cor. of secs. 3, 4, 9, and 10, perpetuated and recorded by Vernon Tracey, Deputy County Surveyor, in 1967, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap marked
	COUNTY SURVEYORS OFFICE T 23 S S 4   S 3 S 9   S 10 R 8 W 1967
	from which the original bearing trees