

1444² County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 8 W.

CHAINS

A fir, 50 ins. diam., bears N. 58° E., 62 lks. dist., with healed blaze and scribe marks T23S R8W visible on bark blaze. (Record distance and slope distance 70 lks.)

A fir, 35 ins. diam., bears S. 16° E., 15 lks. dist., with healed blaze. Remarked by Tracey in 1967; scribe marks T23S R8W S10 CS BT visible on bark blaze. (Record distance 12 lks.)

A fir, 65 ins. diam., bears S. 35° W., 40 lks. dist., with healed blaze and scribe marks T23S R8W S9 visible on bark blaze.

A fir, 48 ins. diam., bears N. 56° W., 18 lks. dist., with healed blaze. Remarked by Tracey in 1967; scribe marks T23S R8W S4 CS BT visible on bark blaze.

and bearing trees marked by Tracey

A fir, 10 ins. diam., bears N. 16° E., 30 lks. Dist., with scribe marks T23S R8W S3 CS BT visible on open double blaze.

A fir, 8 ins. diam., bears S. 16° W., 41 lks. dist., with scribe marks T23S R8W S9 CS BT visible on open double blaze.

Add marks BLM 1967 to brass cap.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, white fir, hemlock, cedar, yew, chinquapin, myrtle, maple, and alder; undergrowth, vine maple, hazel, arrowwood, huckleberry, salmonberry, ceanothus, Oregon grape, salal, and fern.

N. 0° 22' E., bet. secs. 3 and 4.

Ascend 5 ft. along W. slope, through heavy timber and dense undergrowth.

- 2.25 Spur, slopes NW.; desc. 215 ft. over NW. slope.
- 6.90 Ravine, drains W.; asc. 110 ft. over SW. slope.
- 14.75 Spur, slopes W.; desc. 135 ft. over NW. slope.
- 18.75 Bottom of descent, slopes W.; asc. 45 ft. over SW. slope.
- 22.10 Top of ascent, slopes W.; desc. 50 ft. along W. slope.
- 25.20 Bottom of descent, slopes W.; asc. 75 ft. over SW. slope.
- 29.50 Spur, slopes N. 60° W.; desc. 125 ft. over N. slope.
- 32.65 Ravine, drains NW.; asc. 65 ft. over SW. slope.
- 39.83 The 1/4 sec. cor. of secs. 3 and 4, perpetuated and recorded by Vernon Tracey, Deputy County Surveyor, in 1967, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked

COUNTY SURVEYORS OFFICE

T 23 S
 1/4
 S 4 | S 3
 R 8 W
 1967