

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 8 W.

CHAINS

from which the original bearing trees

A fir crown, size indeterminate, bears N. 76° E., 20 lks. dist. no marks remaining.

A fir, 24 ins. diam., bears S. 23° W., 30 lks. dist., with fragmentary scribe marks visible on opened blaze.

and bearing trees marked by Tracey

A hemlock, 8 ins. diam., bears S. 26° E., 10 lks. dist., with scribe marks 1/4 S3 CS BT visible on open double blaze.

A hemlock, 6 ins. diam., bears N. 78° W., 24 lks. dist., with scribe marks 1/4 S4 CS BT visible on open double blaze.

Add marks BLM 1967 to brass cap.

Corner is located on spur, slopes NW.

N. 0° 11' E., beginning new measurement.

Descend 205 ft. over broken NW. slope.

18.40 Heddin Creek, 8 lks. wide, course N. 55° E.; asc. 40 ft. over SE. slope.

20.04 Point for the N 1/16 sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked

N 1/16
S 4 | S 3
1967

from which

A white fir, 10 ins. diam., bears N. 46 1/2° E., 29 lks. dist., mkd. N 1/16 S3 BT.

A white fir, 8 ins. diam., bears N. 55° W., 16 lks. dist., mkd. N 1/16 S4 BT.

Ascend 90 ft. over broken SE. slope.

33.70 Top of ascent, slopes E.; desc. 20 ft. over NE. slope.

35.35 Ravine, drains SE.; asc. 105 ft. over S. slope.

36.60 Enter pasture, edge bears NE. and SW.

42.345 The original closing cor. of secs. 3 and 4, perpetuated and recorded by Milo Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/2 ins. diam, firmly set, projecting 10 ins. above ground, with brass cap marked

COUNTY SURVEYORS OFFICE
R 8 W
CC
S 4 | S 3
T 23 S
1963

from which the original bearing trees

A sawed fir stump, 40 ins. diam., bears S. 52 1/2° E., 272 lks. dist., with fragmentary scribe marks visible on opened blaze. (This tree was also used as the SE. bearing tree for the standard cor. of secs. 3 and 4 established by Gordon and Garnder in 1855.)