

14448County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 11, T. 23 S., R. 8 W.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap marked CC CS II C 40 1967 from which A fir, 13 ins. diam., bears N. 16° W., 85 lks. dist., mkd. T23S R8W S11 CC BT. A fir, 10 ins. diam., bears S. 79° W., 45 lks. dist., mkd. T23S R8W S11 CC BT. Descend 40 ft. over SE. slope. 39.64 The center ¼ sec. cor. of sec. 11. Descend 30 ft. over SE. slope. 40.70 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W. 54.10 Bend of creek, 8 lks. wide, course S. 70° E. from SW.; desc. 5 ft. along creek bottom. 56.80 Same creek, course N. 65° E. 59.00 Same Creek, course S. 35° E. 60.60 Same creek, course N. 40° E.; asc. 5 ft. over NW. slope. 66.30 Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W. 68.20 Creek, 1 lk. wide, course N. 30° W.; asc. 70 ft. over NW. slope. 72.80 Dirt road, 20 lks. wide; bears N. and S. 75.60 Top of ascent, slopes N.; desc. 10 ft. along N. slope. 79.29 The ¼ sec. cor. of sec. 11 only, on the E. bdy. of sec. 11.
	From the S 1/16 sec. cor. of sec. 11 only, on the E. bdy. of sec. 11. N. 89° 58' W., on the E. and W. center line of the SE¼ of sec. 11. Descend 60 ft. over W. slope, through heavy timber and dense undergrowth. 1.00 Dirt road, 15 lks. wide, bears N. and S. 3.00 Creek, 1 lk. wide, course N. 15° E.; asc. 445 ft. over general E. slope. 14.35 Spur, slopes N. 10° W.; desc. 305 ft. over broken NW. slope. 39.69 The center S 1/16 sec. cor. of sec. 11.
	From the W 1/16 sec. cor. of secs. 11 and 14. N. 0° 13' E., on the N. and S. center line of the SW¼ of sec. 11. Ascend 65 ft. over SE. slope, through heavy timber and dense undergrowth.