

Dependent Resurvey, Portion of W. Bdy., T. 29 S., R. 6 W.

CHAINS

A root hole, bears S. 19° W., 46 lks. dist., with a down pine alongside, 36 ins. diam., no marks visible.

A root hole, bears N. $50\frac{1}{2}^{\circ}$ W., 150 lks. dist. (Record, N. 49° W.)

and bearing trees mkd. by J. H. Markham

A madrone, 33 ins. diam., bears N. 3° E., $80\frac{1}{2}$ lks. dist., with scribe marks S31 T29S R6W BT visible on partially healed blaze.

A white oak, 16 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ E., $48\frac{1}{2}$ lks. dist., with scribe marks S6 T30 R6 BT visible on partially healed blaze.

A white oak, 25 ins. diam., bears N. 50° W., 267 lks. dist., with scribe marks 3 29S 7 B visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S
R 7 W | R 6 W
S 36 | S 31

S 1 | S 6
T 30 S
1968

from which a new bearing tree

A fir, 5 ins. diam., bears S. 49° W., $18\frac{1}{2}$ lks. dist., mkd. T30S R7W S1 BT.

Deposit the corner stone alongside the iron post.

From this point, an iron post set by the County Surveyor in 1962, 1 in. diam., protruding 12 ins. above the ground, firmly set, with brass cap mkd. COUNTY SURVEYORS OFFICE T29S R6W R7W S36 S31 S1 S6 T30S 1962, bears S. $23\frac{1}{2}^{\circ}$ E., 0.025 chs. dist.

N. 2° $34'$ E., bet. secs. 31 and 36, marking and blazing the true line.

Ascend 205 ft. over S. slope, through scattering timber and light undergrowth.

13.00 Dirt road, 15 lks. wide, bears E. and W.

18.91 Point for the S 1/16 sec. cor. of sec. 36 only, T. 29 S., R. 7 W. No permanent monument established.

19.58 Point for the S 1/16 sec. cor. of sec. 31 only.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

| S 1/16
| S 31
1968

from which