

14455 County Surveyor's Record, Douglas County, Oregon

T. 25 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of the portion of township 25 south, range 1 west, of the Willamette Meridian, Oregon, pertaining to this resurvey is as follows:

The subdivisional lines were surveyed by Hezekiah H. Johnson, in 1900, as shown on the official plat of survey approved May 6, 1901.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions based on the official record. The re-tracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were chained twice. Only those lines bounding or crossing public lands were blazed.

The directions of the lines were determined by the solar transit method.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and special Instructions dated May 16, 1969.

The geographic position of the corner of secs. 20, 21, 28, and 29, as scaled from the Mace Mountain quadrangle map, published by the United States Geological Survey, in 1955, is as follows:

Latitude $43^{\circ} 22.7' N.$ Longitude $122^{\circ} 49.2' W.$

The mean magnetic declination is $18^{\circ} 20' E.$

Dependent Resurvey, Line Between Sections 20 and 29,
T. 25 S., R. 1 W., Willamette Meridian, Oregon

(Restoring the 1900 survey by Hezekiah H. Johnson)

Beginning at the cor. of secs. 20, 21, 28 and 29, monumented with the original basalt stone, 20 x 10 x 6 ins., mkd. with 4 notches on E., 2 notches on S. edges, and X on top, perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1967, with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 25 S
S 20 | S 21
S 29 | S 28
R 1 W
1967

from which the remaining original bearing trees

A fir snag, 48 ins. diam., bears N. $36\frac{1}{2}^{\circ} E.$, 54 lks. dist., with scribe marks BT visible on open lower blaze. (Record, N. $44^{\circ} E.$, 60 lks.)

A madrone, 17 ins. diam., bears N. $70\frac{1}{2}^{\circ} W.$, 25 lks. dist., with healed blaze. (Record, arbutus, N. $68^{\circ} W.$, 24 lks.)

and bearing trees mkd. by Tracy