

Dependent Resurvey, Line bet. Sections 20 and 29, T. 25 S., R. 1 W.

CHAINS

- A madrone, 10 ins. diam., bears North, 52 lks. dist., with scribe marks T25S R1W S21 CS BT visible on open blaze.
- A fir, 10 ins. diam., bears S. 60 3/4° E., 39 lks. dist., with scribe marks T25S R1W S28 CS BT visible on open blaze.
- A fir, 8 ins. diam., bears S. 85° W., 20 lks. dist., with scribe marks T25S R1W S29 CS BT visible on open blaze.
- A fir, 5 ins. diam., bears N. 38° W., 11 lks. dist., with scribe marks T25S R1W S20 CS BT visible on open blaze.

S. 87° 50' W., bet. secs. 20 and 29, marking and blazing the true line.

Descend 550 ft. over NW. slope, through heavy timber and dense undergrowth.

- 12.75 Creek, 4 lks. wide, course NW.; asc. 520 ft. over broken NE. slope.
- 29.40 Spur, slopes N.; desc. 305 ft. over NW. slope.
- 38.03 Point for the 1/4 sec. cor. of secs. 20 and 29 at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$  S 20  
 $\frac{1}{4}$  S 29  
 T 25 S R 1 W  
 1969

from which

- A fir, 4 ins. diam., bears N. 6° E., 33 lks. dist., mkd. 1/4 S20 BT.
- A hemlock, 7 ins. diam., bears S. 23° E., 52 1/2 lks. dist., mkd. 1/4 S29 BT.

Descend 300 ft. over W. slope.

- 44.40 Creek, 6 lks. wide, course N. 10° E.; asc. 595 ft. over NE. slope.
- 54.25 Dirt road, 20 lks. wide, bears NW. and SE.
- 59.80 Spur, slopes N.; desc. 205 ft. over NW. slope.
- 68.10 Ravine, drains N.; asc. 180 ft. over NE. slope.
- 76.06 The cor. of secs. 19, 20, 29, and 30, perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1967, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 25 S  
 S 19 | S 20  
 S 30 | S 29  
 R 1 W  
 1967