

County Surveyor's Record, Douglas County, Oregon

14460

Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., R. 4 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to bedrock, mkd. X, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 27 S R 4 W
 S 27 | S 26
 S 34 | S 35
 1970

from which

A fir, 40 ins. diam., bears N. 43° E., 25½ lks. dist., mkd. T27S R4 W S26 BT.

A fir, 15 ins. diam., bears S. 56½° W., 78½ lks. dist., mkd. T27S R4W S34 BT.

A fir, 6 ins. diam., bears N. 9 3/4° W., 93½ lks. dist., mkd. T27S R4W S27 BT.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the iron post.

There is no suitable bearing tree available within limits in sec. 35.

From this point

The cor. of secs. 27, 28, 33, and 34, bears N. 89° 38' W., 78.98 chs. distant, perpetuated and recorded by the Douglas County Surveyor's Office in 1959, monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. in the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
 S 28 | S 27
 S 33 | S 34
 T 27 S R 4 W
 1959

from which the remaining original bearing trees:

A cedar stub, 23 ins. diam., bears N. 84° E., 18 lks. dist., with open blaze. No marks visible.

A fir stump, 20 ins. diam., bears N. 50° W., 7 lks. dist., with no marks remaining on decayed blaze. (Record, N. 35° W.)

and bearing trees mkd. by the County Surveyor in 1959

A root hole, bears S. 88½° E., 100 lks. dist., with a down fir, 12 ins. diam., alongside with fragmentary scribe marks visible on open blaze.

A cedar, 18 ins. diam., bears S. 13° E., 51 lks. dist., with fragmentary scribe marks visible on open blaze.

A cedar, 17 ins. diam., bears S. 51° W., 13 lks. dist., with fragmentary scribe marks visible on open blaze.

A yew, 15 ins. diam., bears N. 44½° W., 28 lks. dist., with fragmentary scribe marks visible on open blaze.

Land, mountainous.

Soil, clay loam.

Timber, fir, hemlock, cedar, alder, yew, maple, and oak; undergrowth, salal, vine maple, hazel, and Oregon grape.