

Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., R. 4 W.

CHAINS

From the cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 27 S R 4 W
 $\frac{S 26 | S 25}{S 35 | S 36}$
 1917

from which the remaining original bearing tree:

A hemlock, 35 ins. diam., bears N. 40° W., 24 lks. dist., with fragmentary scribe marks visible on open blaze.

bearing trees mkd. by Elmer F. Strickler in 1917

A cedar, 50 ins. diam., bears S. 66° E., 53 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears S. 58½° W., 37 lks. dist., with healed blaze.

an unrecorded bearing tree

A cedar, 7 ins. diam., bears N. 57° E., 89 lks. dist., with fragmentary scribe marks visible on open blaze.

and a new bearing tree

A hemlock, 10 ins. diam., bears S. 26° W., 27 lks. dist., mkd. T27S R4W S35 BT.

S. 89° 52' W., bet. secs. 26 and 35.

Descend 280 ft. over NW. slope, through scattering timber and dense undergrowth.

18.90 South Fork of Deer Creek, 4 lks. wide, course S. 65° W., asc. 125 ft. over SE. slope.

27.35 Spur, slopes S.; desc. 145 ft. over SW. slope.

39.60 Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4} \frac{S 26}{S 35}$
 T 27 S R 4 W
 1970

from which

A fir, 6 ins. diam., bears N. 50° W., 75½ lks. dist., mkd. ¼ S26 BT.

A fir, 7 ins. diam., bears S. 33½° E., 21 lks. dist., mkd. ¼ S35 BT.

Descend 2 ft. over W. slope.

39.90 Creek, 2 lks. wide, course S.; asc. 25 ft. over SE. slope.

44.40 Spur, slopes S.; desc. 165 ft. over SW. slope.

64.85 Ravine, drains S.; asc. 50 ft. over broken SE. slope.