

Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., R. 4 W.

CHAINS

From the standard cor. of secs. 4, 5, 32, and 33, perpetuated and recorded by the Douglas County Surveyor's Office in 1959, when original corner evidence was existent, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

R T 27 S
4 S 32 | S 33
W S 5 | S 4
T 28 S
1959

from which bearing trees mkd. by the County Surveyor's Office in 1959

A cedar stump, 13 ins. diam., bears N. 43½° E., 180 lks. dist., with scribe marks CS BT visible on open blaze.

A fir, 9 ins. diam., bears N. 57¼° E., 151 lks. dist., with scribe marks T27S R4W S33 CS BT visible on open blaze.

A fir, 13 ins. diam., bears S. 57¼° E., 114 lks. dist., with healed blaze.

A cedar, 15 ins. diam., bears S. 53° W., 151 lks. dist., with healed blaze.

A fir, 35 ins. diam., bears N. 74½° W., 57 lks. dist., with healed blaze.

N. 0° 23' W., bet. secs. 32 and 33.

Ascend 230 ft. over broken S. slope, through scattering timber and moderate undergrowth.

11.60 Ridge, bears N. 85° E., and S. 85° W.; desc. 170 ft. over broken N. slope.

19.925 Point for the S 1/16 sec. cor. of secs. 32 and 33.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

S 1/16
S 32 | S 33
1970

from which bearing trees and a reference monument

A fir, 20 ins. diam., bears S. 64½° E., 117 lks. dist., mkd. S 1/16 S33 BT.

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 10½° E., 15 lks. dist., with brass cap mkd. S 1/16 S33 RM 1970, and an arrow pointing to the corner.

A fir, 18 ins. diam., bears N. 76½° W., 116 lks. dist., mkd. S 1/16 S32 BT.

Corner falls in a ravine, drains W.

Ascend 235 ft. over broken SW. slope.

36.25 Ridge, bears N. 80° E.; and S. 80° W.; desc. 70 ft. over NE. slope.

39.85 Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.