

County Surveyor's Record, Douglas County, Oregon

14164

Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., R. 4 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 32 | S 33
 T 27 S R 4 W
 1970

from which

A fir, 10 ins. diam., bears S. 67½° E., 11½ lks. dist., mkd. $\frac{1}{4}$ S33 BT.

A fir, 12 ins. diam., bears S. 81½° W., 82 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

Descend 315 ft. over broken NE. slope.

56.40
66.55
79.70

Ravine, drains S. 75° W.; asc. 265 ft. over S. slope.
Top of ascent, slopes E.; desc. 175 ft. over NW. slope.
Point for the cor. of secs. 28, 29, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 S R 4 W
 S 29 | S 28
 S 32 | S 33
 1970

from which

A fir, 7 ins. diam., bears N. 20° E., 103 lks. dist., mkd. T27S R4W S28 BT.

A fir, 7 ins. diam., bears S. 20° E., 173 lks. dist., mkd. T27S R4W S33 BT.

A fir, 10 ins. diam., bears S. 6¼° W., 128 lks. dist., mkd. T27S R4W S32 BT.

A fir, 12 ins. diam., bears N. 71 ¾° W., 183 lks. dist., mkd. T27S R4W S29 BT.

From this point

The cor. of secs. 29, 30, 31, and 32, bears N. 89° 21' W. 79.00 chs. distant, perpetuated and recorded by the Douglas County Surveyor's Office in 1959, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
 T 27 S R 4 W
 S 30 | S 29
 S 31 | S 32
 1959

F.O.K.
 S/B 87 M101-26
 O. BENTZ

from which the remaining original bearing tree:

An oak, 20 ins. diam., bears N. 10¼° W., 313 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, N. 8° W., 306 lks. dist.)

and bearing trees mkd. by the County Surveyor's Office in 1959

B.C.
 2 BTs F.O.K.
 by R.B. Kimberling
 APR 12, 1982
 M 91-70