

Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., R. 4 W.

CHAINS

An oak, 12 ins. diam., bears N. $82\frac{1}{4}^{\circ}$ E., 75 lks. dist., with healed blaze.

An oak, 13 ins. diam., bears S. $11\frac{1}{2}^{\circ}$ E., 28 lks. dist., with healed blaze.

A fir, 30 ins. diam., bears S. 73° W., 59 lks. dist., with healed blaze.

An oak, 13 ins. diam., bears N. $1\frac{1}{2}^{\circ}$ W., 44 lks. dist., with healed blaze.

From the same point.

The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, bears N. $0^{\circ} 10'$ E., 39.85 chs. distant, perpetuated and recorded by the Douglas County Surveyor's Office in 1925 when the original bearing trees were existent. The corner is determined from the County Surveyor's bearing trees:

A root hole, bears S. 73° E., 27 lks. dist., with a down decayed fir, 8 ins. diam., alongside, with no marks visible.

A root hole, bears N. 13° W., 20 lks. dist., with a down fir, 10 ins. diam., alongside, with fragmentary scribe marks visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 29 | S 28
 T 27 S R 4 W
 1970

Fnd. OK. by
 R.B. KIMBERLING
 APRIL, 1982
 M 91-70
 M 101-26 8/87

from which new bearing trees

A fir, 10 ins. diam., bears N. $70\frac{1}{4}^{\circ}$ E., 33 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

A fir, 8 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ W., 29 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

Corner falls in old wire fence, bears N. and S.

Land, mountainous.

Soil, clay loam.

Timber, fir, hemlock, alder, oak, yew, and dogwood; undergrowth, hazel, salal, Oregon grape, and arrowwood.

From the cor. of secs. 27, 28, 33, and 34.

S. $89^{\circ} 57'$ W., bet. secs. 28 and 33.

Ascend 290 ft. over broken E. slope, through scattering timber and dense undergrowth.

14.10 Ridge, bears N. 20° W., and S. 20° E.; desc. 130 ft. over W. slope.

19.825 Point for the E $\frac{1}{16}$ sec. cor. of secs. 28 and 33.