

County Surveyor's Record, Douglas County, Oregon

14468

T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of that portion of township 33 south, range 7 west, covered in this resurvey, is as follows:

The east boundary of the township was surveyed by Wells Lake and George W. Hyde, in 1855, as shown on the official plat of survey of T. 33 S., R. 6 W., approved March 31, 1856. The Seventh Standard Parallel South, north boundary of the township, was surveyed by William H. Byars, in 1881, as shown on the official plat of survey of T. 32 S., R. 7 W., approved May 31, 1882. In 1882, Byars surveyed the south boundary and the subdivisional lines, except for the north west portion of the township, as shown on the official plat of survey, approved May 31, 1882. Hans W. Thielsen resurveyed a portion of the subdivisional lines in 1957, as shown on the official plat of survey approved April 3, 1959. The north two and one half miles of the east boundary were resurveyed by Joseph S. Gawron, in 1963-64, as shown on the official plat of survey of T. 33 S., R. 6 W., approved November 1, 1965. In 1963-64, Gawron also remonumented, without survey, the corner of sections 13, 18, 19 and 24, on the east boundary of the township.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Those lines not forming a closure were chained twice. Lines bounding or crossing public lands were blazed.

The survey was executed in accordance with Specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated May 13, 1969, and May 3, 1957, for Groups 688 and 350, Oregon.

The geographic position of the southeast corner of section 32, as scaled from the Galice, Oregon quadrangle map, published by the United States Geological Survey, in 1946, is as follows:

Latitude 42° 39.1' N. Longitude 123° 32.6' W.

The mean magnetic declination is 19° 12' E.

Dependent Resurvey of the 7th Stan. Par. S.,
Portion of the S. Bdy. of T. 32 S., R. 6 W.,
Willamette Meridian, Oregon

(Restoring the 1885 survey by Wells Lake
and George W. Hyde)

From the true point for the standard cor. of Tps. 33 S., Rs 6 and 7 W., in Cow Creek, as described in the official record of a 1963-64 resurvey.

S. 89° 31' W., on the S. bdy. of sec. 31, marking and blazing the true line.

0.50 Left bank of Cow Creek, bears N. 65° W. and S. 65° E.; asc. 5 ft. over open bottom land.