

Dependent Resurvey, 7th Stan. Par. S., Portion of S. Bdy., T. 32 S., R. 7 W.

CHAINS

3.00 Paved road, 40 lks. wide, bears N. 70° W. and S. 70° E.

9.77 Point for the standard cor. of Tps. 32 S., Rs. 6 and 7 W., at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.

Dependent Resurvey of the 7th Stan. Par. S.,
Portion of the S. Bdy. of T. 32 S., R. 7 W.

(Restoring the 1881 survey by William H. Byars)

From the point for the standard cor. of Tps. 32 S., Rs. 6 and 7 W.
S. 89° 31' W., on the S. bdy. of sec. 36.

Across open level land.

27.23 Enter timber and dense undergrowth, edge bears N. and S.

29.30 The $\frac{1}{4}$ sec. cor. of sec. 1 only, established and recorded by Douglas J. Theno, Registered Engineer, No. 2968, in 1950, at midpoint on the N. bdy. of sec. 1, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 12 ins. above ground, from which bearing trees mkd. by Theno:

A fir, 15 ins. diam., bears N. 37° E., 2 lks dist., with scribe marks $\frac{1}{4}$ S visible on opened blaze.

A fir, 17 ins. diam., bears S. 69° E., 42 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.

$\frac{1}{4}$ S 1
T 33 S R 7 W
1969

from which a new bearing tree

A live oak, 6 ins. diam., bears S. 72 $\frac{1}{2}$ ° W., 46 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

Reset iron pipe alongside iron post.

S. 89° 31' W., beginning new measurement.

Descend 5 ft. over nearly level bottom land.

10.295 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, on the S. bdy. of T. 32 S., R. 7 W., at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.

Continue over nearly level bottom land.

10.49 From this point, an iron pipe, of which I have no record, 2 ins. diam., firmly set, extending 36 ins. above ground, bears North, 0.02 chs. distant.