

County Surveyor's Record, Douglas County, Oregon

14470

Dependent Resurvey, 7th Stan. Par. S., Portion of S. Bdy., T. 32 S., R. 7 W.

CHAINS	<p>Ascend 130 ft. over NE. slope.</p>
18.20	Spur, slopes N.; desc. 125 ft. over NW. slope.
34.45	Paved road, 40 lks. wide, bears N. 70° E. and S. 70° W.
39.07	<p>The original closing cor. of secs. 1 and 2, perpetuated and recorded by Marvin C. Ramsey, Registered Land Surveyor, No. 404, in 1965, with an iron pipe, 2 ins. diam., firmly set, extending 8 ins. above ground, with bronze washer in top, mkd. RS 404, from which the original bearing trees:</p> <p style="margin-left: 40px;">A sawed cedar stump, 36 ins. diam., bears S. 35° E., 20 lks. dist., with no marks visible.</p> <p style="margin-left: 40px;">A sawed fir stump, 28 ins. diam., bears S. 44° W., 28 lks. dist., with no marks visible.</p> <p style="margin-left: 40px;">The rotted remains of a fir stump, size indeterminate, bears N. 60° W., 24 lks. dist., with no marks visible. (Record, N. 65° W., 21 lks.)</p> <p>and bearing trees mkd. by Ramsey</p> <p style="margin-left: 40px;">A fir snag, 10 ins. diam., bears S. 57° E., 36 lks. dist., with open blaze.</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 10° W., 10 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by John Powell, Deputy County Surveyor, in 1967</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 82° E., 33 lks. dist., with open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 32 S R 7 W</p> <p style="margin-left: 40px;">S 36</p> <hr style="width: 50%; margin: 0 auto;"/> <p style="margin-left: 40px;">S 2 S 1</p> <p>T 33 S R 7 W</p> <p style="margin-left: 40px;">CC</p> <p style="margin-left: 40px;">1969</p> </div> <p>Reset iron pipe alongside iron post.</p> <p>From this point an iron pipe 1 in. diam., firmly set, projecting 6 ins. above ground, of which I have no record, bears S. 61½° E., 0.06 chs. distant.</p> <p>Across level bottom land, through scattering timber and dense undergrowth.</p>
49.89	<p>The original standard cor. of secs. 35 and 36, perpetuated and recorded by Milner L. Larson, Registered Engineer, No. 3642, in 1967, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 2 ins. above ground, from which the original bearing trees:</p> <p style="margin-left: 40px;">A sawed fir stump, 30 ins. diam., bears N. 30° E., 14 lks. dist., with no marks visible.</p>