

# County Surveyor's Record, Douglas County, Oregon

14174

Dependent Resurvey, Portion of S. Boundary, T. 33 S., R. 7 W.

CHAINS

*Dependent Resurvey*

Land, mountainous.  
Soil, rocky clay loam.  
Timber, fir, cedar, pine, madrone, chinquapin, oak, alder;  
undergrowth, vine maple, manzanita, ceanothus, poison oak,  
devil's club, and whitethorn.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the 1882 survey by William H. Byars)

From the cor. of secs. 13, 18, 19 and 24.

S. 89° 17' W., bet. secs. 13 and 24, marking and blazing  
the true line.

Descend 5 ft. over SW. slope, through heavy timber and  
dense undergrowth.

- 1.00 Rovaine, drains S.; asc. 5 ft. over SE. slope.
- 2.45 Spur, slopes S.; desc. 110 ft. over SW. slope.
- 8.65 Creek, 1 lk. wide, course S. 25° E.; asc. 240 ft. over SE. slope.
- 19.49 The E 1/16 sec. cor. of secs. 13 and 24, established and recorded  
by Richard L. Templin, Jr., Registered Engineer, No. 3024, in 1955,  
monumented with an iron pipe, 1 in. diam., firmly set, projecting  
8 ins. above ground, from which:
  - A fir, 14 ins. diam., bears N. 72½° E., 22 lks. dist.,  
with healed blaze.
  - A fir, 13 ins. diam., bears S. 39° W., 7 lks. dist.,  
with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the  
ground, with brass cap mtd.

$$\begin{array}{r} \text{E } 1/16 \text{ } \frac{\text{S } 13}{\text{S } 24} \\ 1969' \end{array}$$

Deposit iron pipe inside the ironpost.

---

S. 89° 17' W., beginning new measurement.

Ascend 305 ft. over SE. slope.
- 12.10 Ridge, bears N. 15° E. and S. 15° W.; also dirt road, 10 lks. wide,  
bears same as ridge; desc. 215 ft. over SW. slope.
- 13.70 Dirt road, 10 lks. wide, bears N. 20° W. and S. 20° E.
- 19.49 The ¼ sec. cor. of secs. 13 and 24, established by Richard L. Templin,  
Jr. Registered Engineer, No. 3024, in 1955, monumented with an iron  
pipe, ¾ in. diam., firmly set, projecting 6 ins. above ground,  
from which:
  - A fir, 35 ins. diam., bears N. 9° E., 45½ lks. dist., with  
healed blaze.