

County Surveyor's Record, Douglas County, Oregon

14478

Dependent Resurvey, Portion of Subdivisional Lines, T. 33 S., R. 7 W.

CHAINS

A fir, 21 ins. diam., bears N. 49° W., 22½ lks. dist.,
with pitched over blaze.

A fir, 18 ins. diam., bears S. 8° W., 70 lks. dist.,
with pitched over blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd.

T 33 S R 7 W
¼ S 12
S 13
1969

Deposit iron pipe alongside the iron post.

N. 89° 22' W., beginning new measurement.

Descend 45 ft. over SW. slope.

- 6.35 Rattlesnake Creek, 10 lks. wide, course N. 25° W.; asc. 385
ft. over NE. slope.
- 28.35 Spur, slopes N.; desc. 200 ft. over NW. slope.
- 34.00 Creek, 1 lk. wide, course N.10° W.; asc. 130 ft. over NE. slope.
- 38.80 Spur, slopes N. 30° W.; desc. 5 ft. over NW. slope.
- 39.29 The cor. of secs. 11, 12, 13, and 14.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, cedar, maple, oak, alder, chinquapin,
madrone, pine; undergrowth, vine maple, poison oak, devil's club,
manzanita, ceanouthus, and whitethorn.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.
S. 83° 12' W., bet. secs. 1 and 12.

Descend 510 ft. over broken SW. slope, through scattering
timber and dense undergrowth.

- 39.54 Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate
distance; there is no remaining evidence of the original
corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd.

T 33 S R 7 W
¼ S 1
S 12
1969

from which

A pine, 4 ins. diam., bears N. 13° E., 39 lks. dist.,
mkd. X BT.

A madrone, 5 ins. diam., bears S. 66° W., 32½ lks. dist,
mkd. ¼ S12 BT.