

County Surveyor's Record, Douglas County, Oregon

14480

Dependent Resurvey, Portion of Subdivisional Lines, T. 33 S., R. 7 W.

CHAINS	
14.60	<p>Creek, 1 lk. wide, course S. 20° W.; asc 110 ft. over SW. slope.</p>
22.14	<p>The S 1/16 sec. cor. of secs. 1 and 2, established and recorded by Marvin C. Ramsey, Registered Land Surveyor, No. 404, in 1965, monumented with an iron pipe, 1½ ins. diam., firmly set, extending 8 ins. above the ground, with bronze washer in top, mkd. RS 404, from which bearing trees mkd. by Ramsey:</p> <p style="margin-left: 40px;">A fir, 19 ins. diam., bears S. 17° E., 217 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A madrone, 11 ins. diam., bears S. 60° W., 72 lks. dist., with scribe marks S 1/16 S2 RS 404 BT visible on bark.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>S 1/16</p> <p>S 2 S 1</p> <p>1969</p> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A madrone, 6 ins. diam., bears N. 65° W., 33 lks. dist., mkd. S 1/16 S2 BT.</p> <p>Insert iron pipe inside iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 12' E., beginning new measurement.</p> <p>Ascend 440 ft. over SW. slope.</p>
22.03	<p>The ¼ sec. cor. of secs. 1 and 2, reestablished and recorded by Marvin C. Ramsey, Registered Land Surveyor, No. 404, in 1965, by proportionate methods; there is no remaining evidence of the original corner. The corner point is monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with bronze washer in top, mkd. RS 404, from which bearing trees mkd. by Ramsey:</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears S. 12° E., 112 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A madrone, 7 ins. diam., bears N. 84° W., 34 lks. dist., with scribe marks ¼ S2 RS 404 BT visible on bark.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>T 33 S R 7 W</p> <p>¼</p> <p>S 2 S 1</p> <p>1969</p> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A chinquapin, 11 ins. diam., bears S. 67¼° W., 31 lks. dist., mkd. ¼ S2 BT.</p>