

Dependent Resurvey, Portion of Subdivisional Lines, T. 33 S., R. 7 W.

CHAINS

Insert iron pipe inside iron post.

N. 0° 7' E., beginning new measurement.

Ascend 30 ft. over SW. slope.

1.70 Spur, slopes W.; desc. 410 ft. over NW. slope. Enter along W. edge of heavy timber, edge bears N. and E.

11.85 Creek, 1 lk. wide, course W.; asc. 60 ft. over SW. slope.

14.50 Spur, slopes W.; desc. 70 ft. over NW. slope.

17.00 Ravine, drains W.; asc. 55 ft. over SW. slope.

22.06 The N 1/16 sec. cor. of secs. 1 and 2, established and recorded by Marvin C. Ramsey, Registered Land Surveyor, No 404, in 1965, monumented with an iron pipe, 1 in. diam., firmly set, extending 2 ins. above the ground, with bronze washer in top, mkd. RS 404, from which bearing trees mkd. by Ramsey:

A pine, 11 ins. diam., bears N. 34° E., 46 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 84° W., 65½ lks. dist., with healed blaze.

The corner is located at top of ascent, slopes W.

N 0° 11' E., beginning new measurement.

Descend 415 ft. over NW. slope.

22.93 Paved road, 40 lks. wide, bears N. 70° E. and W.

23.72 The closing cor. of secs. 1 and 2.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, madrone, oak, alder, and chinquapin; undergrowth, vine maple, whitethorn, ceanothus, manzanita, devil's club, and poison oak.

From the cor. of secs. 5, 6, 31 and 32 on S. bdy. of Tp.

N. 0° 05' W., bet. secs. 31 and 32

Descend 55 ft. over N. slope, through heavy timber and dense undergrowth.

9.50 Grave Creek, 100 lks. wide, course N. 60° W.; asc. 85 ft. over SW. slope.

10.90 Grave Creek Road, 50 lks. wide, bears N. 60° W. and S. 60° E.

15.00 Top of ascent, slopes W.; desc. slightly over nearly level land.

20.31 Point for the S 1/16 sec. cor. of secs. 31 and 32.

Set an iron post, 28 ins. long 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 31/S 32
1969

*Josephine
County
Sept 24*

*See Josephine
County for field
notes B.S.M.
Pages 217-218.*