

Subdivision of Sec. 1, T. 33 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 7 W
C ¼ S 1
1969

from which

A fir, 41 ins. diam., bears N. 74½° E., 70 lks. dist., mkd. C ¼ S 1 BT.

A fir, 15 ins. diam., bears S. 72° W., 76 lks. dist., mkd. C ¼ S 1 BT.

Descend 755 ft. over NE. slope, changing to N. slope.

62.50 Creek, 1 lk. wide, course N. 50° E.; asc 10 ft. over SE. slope.

63.57 Point for the center N 1/16 sec. cor. of sec. 1.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with btass cap mkd.

N 1/16 $\begin{matrix} C \\ | \\ S \\ | \\ C \end{matrix}$ 1
1969

from which

A white fir, 6 ins. diam., bears S. 62° E., 22½ lks. dist., mkd. CN 1/16 S 1 BT.

A fir, 25 ins. diam., bears N. 27° W., 24 lks. dist., mkd. CN 1/16 S 1 BT.

The corner is located at the SW. corner of a logged area.

Ascend 15 ft. over SE. slope, along W. edge of logged area.

68.00 Top of ascent, slopes E.; desc. 215 ft. over NE. slope.

85.57 The ¼ Sec. cor. of sec. 1 only.

From the ¼ sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp. S. 85° 49' W., on the E. and W. center line of sec. 1.

Ascend 155 ft. over NE. slope, through heavy timber and dense undergrowth.

6.20 Spur, slopes N; desc. 275 ft. over NW. slope.

17.20 Creek, 1 lk. wide, course N.; asc 100 ft. over NE. slope.

20.30 Spur, slopes N.; desc. 45 ft. over NW. slope.

22.30 Ravine, drains N.; asc. 395 ft. over NE. slope.

39.29 The center ¼ sec. cor. of sec. 1.

Ascend 105 ft. over NE. slope.