

14487 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 23 S., R. 8 W.

CHAINS

A fir, 24 ins. diam., bears S. 34° W., 32 lks. dist., with healed blaze.

A fir, 32 ins. diam., bears N. 82° W., 16 lks. dist., with healed blaze.

Land, mountainous.

Soil, clay loam.

Timber, fir, hemlock, oak, maple, yew, cedar, dogwood, and cascara; undergrowth, Oregon grape, hazel, fern, poison oak, and salal.

North, along the W. bdy. of sec. 13.

Ascend 85 ft. over S. slope.

3.90 Spur ridge, bears NW. and SE.; asc. 105 ft. over broken SE. slope.

15.15 Spur ridge, bears N. 15° E. and S. 15° W.; desc. 75 ft. over NW. sope.

19.71 Point for the S. $1/16$ sec. cor. of sec. 14 only.

Set an iron Post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S $1/16$ |
S 14 |
1970

from which

A chinquapin, 9 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ W., 33 lks. dist., mkd. S $1/16$ S14 BT on bark.

A madrone, 13 ins. diam., bears N. 41° W., 33 lks. dist., mkd. S $1/16$ S14 BT on bark.

Ascend 515 ft. over broken S. slope.

39.42 Point for the $\frac{1}{4}$ sec. cor. 14 only, at mid point latitudinally, on the E. bdy. of sec. 14.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 14 |
T 23 S |
R 8 W |
1970

from which

A fir, 8 ins. diam., bears S. 88° W., 33 lks. dist., mkd. X.

A fir, 15 ins. diam., bears N. 61° W., 16 lks. dist., mkd. $\frac{1}{4}$ S14 BT.

Ascend 1 ft. over SW. slope.

39.53 The $\frac{1}{4}$ sec. cor. of sec. 13 only, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, mkd. and witnessed as described in the official record of the 1968 dependent resurvey.

N. $0^{\circ} 18'$ E., beginning new measurement.

Descend 305 ft. over broken NE. slope.