

Dependent Resurvey, Subdivisional Lines, T. 23 S., R. 8 W.

CHAINS

56.35 Spur ridge, bears N. 20° W. and S. 20° E.; desc. 225 ft. over W. slope.

63.00 Creek, 2 lks. wide, course N.; asc. 415 ft. over NE. slope.

77.90 Spur ridge, bears N. and S.; desc. 110 ft. over NW. slope.

81.83 The cor. of secs. 12 and 13 only, on the E. bdy. of sec. 11.

Land, mountainous.  
Soil, clay loam.  
Timber, fir, hemlock, cedar, oak, maple, and dogwood; undergrowth, scotch broom, salal, arrowwood, fern, and poison oak.

Subdivision of Section 13, T. 23 S., R. 8 W.,  
Willamette Meridian, Oregon

From the  $\frac{1}{4}$  sec. cor. of secs. 13 and 24.

N. 0° 42' E., on the N. and S. center line of sec. 13.

Ascend 270 ft. over broken S. slope, through heavy timber and dense undergrowth.

36.10 Dirt road, 20 lks. wide, bears N. 70° W. and S. 70° E.

37.55 Spur ridge, bears N. 70° W. and S. 70° E.; desc. 85 ft. over broken NE. slope.

39.755 Point for the center  $\frac{1}{4}$  sec. cor. of sec. 13, at intersection with the E. and W. center line of sec. 13.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

C  $\frac{1}{4}$  S 13  
1970

from which

A fir, 30 ins. diam., bears S. 57° E., 47 lks. dist., mkd.  
C  $\frac{1}{4}$  S13 BT.

A fir, 34 ins. diam., bears N. 58 $\frac{1}{2}$ ° W., 70 lks. dist., mkd.  
C  $\frac{1}{4}$  S13 BT.

Descend 375 ft. over N. slope.

44.60 Dirt road, 20 lks. wide, bears N. 70° W. and S. 70° E.

59.525 Point for the center N 1/16 sec. cor. of sec. 13.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

C  
N 1/16 | S 13  
C  
1970

from which