

County Surveyor's Record, Douglas County, Oregon 14490

Subdivision of Section 13, T. 23 S., R. 8 W.

CHAINS	
	<p>A fir, 14 ins. diam., bears N. 88° E., 50 lks. dist., mkd. CN 1/16 S13 BT.</p> <p>A fir, 24 ins. diam., bears S. 25° W., 63½ lks. dist., mkd. CN 1/16 S13 BT.</p> <p>Descend 180 ft. over broken N. slope.</p>
71.65	Ravine, drains N. 30° E.; desc. 25 ft. over N. slope.
79.875	The ¼ sec. cor. of secs. 12 and 13.
	<p>From the ¼ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron pipe, 2½ ins. diam., firmly set, projecting 6 ins. above ground, mkd. and witnessed as described in the official record of the 1964 dependent resurvey.</p> <p>S. 89° 19' W., on the E. and W. center line of sec. 13.</p> <p>Ascend 90 ft. over NE. slope, through heavy timber and dense undergrowth.</p>
3.20	Spur, slopes N. 10° W.; desc. 85 ft. over NW. slope
6.40	Ravine, drains N. 45° E.; asc. 105 ft. over NE. slope.
10.20	Spur, slopes N.; desc. 20 ft. over NW. slope.
11.75	Ravine, drains N. 60° E.; asc. 525 ft. over NE. slope.
40.88	The center ¼ sec. cor. of sec. 13.
	Ascend 45 ft. over NE. slope.
44.30	Spur ridge, bears N. 55° W. and S. 55° E.; asc. 335 ft. over NE. slope.
75.05	Dirt road, 15 lks. wide, bears N. 60° W. and S. 60° E.
80.05	Spur ridge, bears N. 70° W. and S. 70° E.; desc. 15 ft. over W. slope.
81.565	The ¼ sec. cor. of sec. 13 only.
	<p>From the N 1/16 sec. cor. of secs. 13 and 18 on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, mkd. and witnessed as described in the official record of the 1964 dependent resurvey.</p> <p>S. 89° 33' W., on the E. and W. center line of the NE¼ of sec. 13.</p> <p>Descend 25 ft. over W. slope, through heavy timber and dense undergrowth.</p>
.60	Dirt road, 30 lks. wide, bears N. 50° W. and S. 50° E.
7.60	Creek, 15 lks. wide, course N.; asc. 60 ft. over broken E. slope.
26.45	Ravine, drains N. 30° E.; asc. 220 ft. over NE. slope.
40.94	The center N. 1/16 sec. cor. of sec. 13.