

T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The history of surveys in that portion of township 31 south, range 7 west, Willamette Meridian, Oregon, covered by this resurvey is as follows:

The corner of townships 30 and 31 south, ranges 6 and 7 west was established by Addison R. Flint in 1855 as shown on the official plat of survey in township 30 south, range 6 west, approved December 10, 1855. In the same year Wells Lake and George W. Hyde surveyed the east boundary of the township. William H. Byars surveyed the east five miles of the north boundary and a portion of the subdivisional in 1872, as shown on the official plat of survey approved January 8, 1873. In 1882, Byars surveyed the west boundary the north boundary of section 6, a portion of the subdivisional lines, and resurveyed the east boundary as shown on the official plat of survey approved October 5, 1882. John M. Jelley remonumented the corner of townships 30 and 31 south, ranges 6 and 7 west as shown on the official plat of survey in township 31 south, range 6 west, accepted July 12, 1966.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions, based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding, or crossing, public lands were blazed. All lines not forming closures were chained twice.

The resurvey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1947, and Special Instructions, dated August 15, 1968, and May 3, 1957.

The directions of lines were determined by solar transit methods.

The geographic position of the corner of section 13, 18, 19 and 24, as scaled from the Canyonville, Oregon, quadrangle map, prepared by the United States Geological Survey, in 1954, is as follows:

Latitude 42° 52.2' N. Longitude 123° 28.0' W.

The mean magnetic declination is 18° 22' E.

Dependent Resurvey of a Portion of the East Boundary T. 31 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the 1882 survey by William H. Byars)

From the cor. of secs. 13, 18, 19, and 24, perpetuated and recorded by the Douglas County Surveyor in 1962, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

	T	31	S	R
R	7	S	13	S
			18	6
W	S	24	S	19
				W
				1962

from which the remaining original bearing trees: