

Dependent Resurvey, Portion of E. Bdy., T. 31 S., R. 7 W.

CHAINS

A cedar, 32 ins. diam., bears N. 22° E., 62 lks. dist., with fragmentary scribe marks visible on opened blaze.

A fir, 65 ins. diam., bears S. 72° W., 50 lks. dist., with fragmentary scribe marks visible on bark blaze.

A fir, 35 ins. diam., bears N. 20° W., 20 lks. dist., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by the County Surveyor

A fir, 22 ins. diam., bears S. 8° E., 44 lks. dist., with fragmentary scribe marks visible on open blaze.

A fir, 15 ins. diam., bears S. 44½° W., 69½ lks. dist., with fragmentary scribe marks visible on open blaze.

N. 0° 29' E., bet. secs. 13 and 18, marking the true line.

Ascend 30 ft. over SE. slope, through moderate timber and undergrowth.

2.15 Jeep road, 10 lks. wide, bears E. and W.

3.85 Ridge, bears E. and W.; desc. 500 ft. over NW. slope.

16.25 Ravine, drains N. 30° E.; desc. 330 ft. over NE. slope.

25.20 Creek, 1 lk. wide, course N. 70° E.; asc. 5 ft. over E. slope.

26.85 Spur, slopes E.; desc. 145 ft. over NE. slope.

30.30 Creek, 3 lks. wide, course N. 10° W.; asc. 120 ft. over SW. slope.

33.25 Top of ascent, slopes W.; desc. 40 ft. over NW. slope.

40.77 Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 13 | S 18
 R 7 W | R 6 W
 T 31 S
 1969

from which

A fir, 12 ins. diam., bears S. 22½° E., 84 lks. dist., mkd. ¼ S18 BT.

A fir, 24 ins. diam., bears S. 8½° W., 67½ lks. dist., mkd. ¼ S13 BT.

Descend 100 ft. over NW. slope.

44.95 Creek, 3 lks. wide, course N. 30° E.; asc. 30 ft. over SE. slope.

47.30 Spur, slopes E.; desc. 125 ft. over NE. slope.

54.60 Creek, 5 lks. wide, course N. 30° W.; asc. 60 ft. over SW. slope.